# **Macbond Arctic®**

### **Engineered Tapes & Laminates**















Macbond Arctic's unique adhesive formulation offers aggressive peel and tack at temperatures as low as -10F. Let Arctic extend your building season or most challenging cold temperature application today!







## **Macbond Arctic®**


## **Engineered Tapes & Laminates**

Minimum App Temperature -10

-10° (-23°C)


Service Range:

-65°F to 150°F (-54°C to 65.5°C)



#### **Double-Coated Tapes**

Construction									Master Roll		0	1 55	HDPE	Shear
Part Number	Carrier	Adhesive		at Weight Caliper Mils Mils			End Use	Width	Length	Weight / MSI	Stock/MTO	Pee	Peel	Sh
			Liner	Un- wind	Carrier & Adhesive	Liner	Release	Wie	Len	We	Şŧ	Lbs/ in	Lbs/ in	Hours
ARTX1161	.5mil PET	Arctic MX10	1.5	1.5	3.5	72# White PCK	Medium	60"	750'	0.33	S	7.6	7.3	75+
ARTX1162	.5mil PET		2.0	2.0	4.5		Medium	60"	750'	0.35	S	7.6	7.3	75+



#### **Transfer Adhesives**

Construction								Master Roll		0	SS I	HDPE	Shear
Part Number	Carrier	Adhesive	Coat Weight Mils	Caliper Mils	Liner	End Use	Width	Length	Weight / MSI	Stock/MTO	Peel	Peel	Sh
				Liner & Adhesive		Release	Wie	Len			Lbs/ in	Lbs/ in	Hours
ARTX1062	NA	Arctic MX10	2.0	6.4	80# White SCK	Medium	60"	540'	0.33	М	6.2	6	75+

For Regulatory Information, please visit www.mactac.com for all product regulatory compliance. For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates.

For Technical Data Sheets please visit www.mactac.com/industrialtapes.



 $\verb|email| mactac.americas@mactac.com| www.mactac.com/industrial tapes$