

PERMACOLOR® RAYZor™ OVERLAMINATES



High-performance laminates add super sizzle to all your conformable graphics.

Graphics that Rock!



Ultra-Matte Wraps



High Gloss Vehicle Graphics



Wall Graphics

SERIOUSLY COOL TECHNOLOGY



A Bemis Company

Two finishes, high gloss for a high shine paint-like image and zero glare matte to duplicate the trendiest finish in the automotive market today.

What It is.

PERMACOLOR® RAYZor™ overlaminates are ultra-conformable 1.5 mil cast vinyls in matte and gloss finishes. The optically clear adhesive is protected with a clear film release liner for flawless, distortion-free lamination.

How PERMACOLOR® RAYZor™ works for you.

PERMACOLOR RAYZor laminates are designed for use on indoor and outdoor graphics needing extended durability and flexibility. UV protection is built into PERMACOLOR RAYZor to help prevent ink fade caused by ultra-violet light. PERMACOLOR RAYZor laminates are ideal for use with MACTac's IMAGin® B•free™ products JT5500 and JT5500 PRO. Choose them for partial and full vehicle wraps, fleet and marine markings, outdoor durable signage, wall graphics and perforated window graphics. PERMACOLOR RAYZor laminates also improve handling of any thin-gauge wrap film.

PERMACOLOR®

| Product | Gauge | Adhesive | Liner |
|--|--------------------|-------------------|-------------------|
| LF3630 | 1.5 mil cast matte | Acrylic Permanent | 1.2 mil polyester |
| LF3640 | 1.5 mil cast gloss | Acrylic Permanent | 1.2 mil polyester |
| Durability | | | |
| <ul style="list-style-type: none"> - Seven year outdoor durability. - Use-life estimate based on accelerated age studies on vertical applications under "normal" environmental conditions. - Severe environmental conditions will reduce use life. - Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to MACTac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit www.MACTac.com to download. | | | |
| Temperature Ranges | | | |
| <ul style="list-style-type: none"> - Minimum Application: +50° F (+10° C) - End Use: -40° to 180° F (-40° to 82° C) | | | |
| Shelf Life | | | |
| Two years when stored at 75°F (24°C) and 50% relative humidity in the original package. | | | |
| <i>Overlaminating with Permacolor® clear films enhances color and protects against UV fade</i> | | | |



SERIOUSLY COOL TECHNOLOGY

