

# PERMACOLOR® *Enhancers*

Digital Overlaminates



Add a little sparkle to your printed and cut graphics.

## Graphics that Rock!



Enhance Base Color



Dazzling Vehicle Graphics



High-Impact Sparkle

SERIOUSLY COOL TECHNOLOGY



A Bemis Company

Silver, Brilliant Crystal, and Prism Metallic Enhancers laminating films will make your graphics dazzle.

**What It Is.**

PERMACOLOR® Enhancer overlaminates are conformable 2.5 to 3.0 mil cast vinyls in Silver Metallic, Brilliant Crystal, and Prism Metallic finishes. With a tough acrylic adhesive, these dazzling overlaminates are designed for flat and moderately curved surfaces. Three shimmering finishes, so you can create fresh, exciting graphics, time after time.

**How PERMACOLOR Enhancers Work for You.**

PERMACOLOR Enhancer laminates are designed to add an elegant finish to high quality indoor and outdoor graphics needing extended durability. UV protection is built into the laminate to help prevent ink fade caused by ultra-violet light. Enhancer laminates are ideal for use with MACtac’s IMAGin® B•free™ products JT5500 and JT5500 PRO, other outdoor durable media, and cut vinyl. Use them for partial vehicle wraps, fleet and marine markings, indoor and outdoor durable signage.

PERMACOLOR®

Product	Description	Adhesive	Liner
CY639800	3.0 mil Silver Metallic Cast Vinyl	Permanent Acrylic	78# Bleached White Kraft
CY639801	2.5 mil Brilliant Crystal Met. Cast Vinyl	Permanent Acrylic	78# Bleached White Kraft
CY639802	3.0 mil Prism Metallic Cast Vinyl	Permanent Acrylic	78# Bleached White Kraft

**Durability**

- Five year outdoor durability.
- Use-life estimate based on accelerated age studies on vertical applications under “normal” environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to MACtac® Product Performance Guides and Technical Assistance Bulletins prior to use.

**Temperature Ranges**

- Minimum Application: +40° F (+5°C)
- End Use: -50° to 225° F (-45° to 107° C)

**Shelf Life**

Two years when stored at 75°F (24°C) and 50% relative humidity in the original package.

*Overlaminating with Permacolor® clear films enhances color and protects against UV fade*



SERIOUSLY COOL TECHNOLOGY

