

JT5800 *B*·free™

BUBBLE FREE DIGITAL MEDIA



New Intermediate Film provides Indoor/Outdoor application versatility.

Graphics that Rock!



Really cool cooler graphics



Outdoor events posters



Museum and special event displays

SERIOUSLY **COOL** TECHNOLOGY



A Bemis Company

Excellent print quality for a wide range of applications, from short term indoor to mid-term outdoor advertising and promotional signs. Bubble-free technology makes installation a breeze!

What you're looking for.

B•free™ 5800 (JT5829BFD MQ) is a 3.7 mil gloss white, vinyl film you can rely on for all those great "bread & butter" jobs. Its ultra-smooth, gloss white surface delivers high impact color graphics. And it's coated with a quick-building, permanent, opaque acrylic pressure sensitive adhesive - with advanced air-egress technology - and an 80# polycoated liner.

Where B•free 5800 works for you.

Use it for all wide-format processes - eco-solvent, solvent-based and UV-cured ink jet printing. B•free 5800 is designed for use on flat or simple curved surfaces - indoor and outdoor signage, displays and point of purchase promotions.

- **Advanced air egress technology is omni-directional - squeegee any direction and air pockets disappear**
 - **Microstructured adhesive allows easy liner removal, without stretching media**
 - **Panel alignment is fast and easy**
 - **Facestock strength provides for easy removal**
 - **Overlaminating with Permacolor® ColorGard™ clear films enhances color and protects against UV fade**
- Go to www.MACtac.com to download your ICC profile.

Product	Gauge	Adhesive	Liner
JT5829BFD MQ	3.7 mil gloss white	Opaque Acrylic Permanent	80# polycoated

Durability

- Indoor and three-year outdoor durability.
- Use-life estimate based on accelerated age studies on vertical applications under "normal" environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to MACtac® Product Performance Guides and Technical Assistance Bulletins prior to use. *Visit www.MACtac.com to download.*

Temperature Ranges

- Minimum Application: +50°F (+10°C)
- End Use: -20° to 194°F (-29° to 90°C)

Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.

JT5800 B•free™
BUBBLE FREE DIGITAL MEDIA



SERIOUSLY COOL TECHNOLOGY

