



A Bemis Company

# Basket of 12

## MACtac® Products You Should Know

### Competitive Product Cross Reference

	Product	Ct/Wt Mil Field Factory	Carrier	Master Roll Sample Roll	MSI	Peel	Tack	Temp Max	Performance	Description	Liner	Recommended For	Avery	3M	Adchem	CCT	Scapa Tesa
Rubber DC	<b>IB1178</b>	1.2/1.2	1/2 mil PET	54"x750' 6" x 30'	486	8.0/8.0	10.0/10.0	180°F	Good	Cost effective general purpose bonding to smooth surfaces	60# white SCK	Any general performance bond	8368/FT-B			M1207	
	<b>IB1190A</b>	1.2/1.8	1/2 mil PET	54"x750' 6" x 30'	486	8.5/9.5	10.5/12.5	180°F	Better	Great tack and peel on a wide variety of substrates especially non-plasticized foams and gaskets. A cost effective solution to foam bonding and other more challenging substrates	60# white SCK	Foam Fabrication, Gasketing, PET Urethane foam, PE Foam, sponge, plastic, rubber, compressed sheet	8326/FT-B			M1212	
	<b>IB1200A</b>	2.7/2.7	1 mil PP	54"x750' 6" x 30'	486	11.5/12.0	6.0/4.5	180°F	Best!	Heavy coat-weight for high performance requirements. 1 mil PP carrier for excellent conformability while increasing the integrity of your bond	60# white SCK	Very high performance applications OEM Specification, PE Foam, sponge, plastic, rubber, cork, compressed sheet				M1208	
DC Foam Tape	<b>IM1900A</b>	1.8/1.8	1/32" white PE foam	54"x216' 1" x 5'	140	***	***	150°F	Good	General purpose bonding and mounting between irregular and LSE substrates.	80# white SCK	Appliance / assembly aid	2132	4462		FT1800	
	<b>IM1800A</b>	2.7/2.7	1/32" white PE foam	54"x216' 1" x 5'	140	***	***	150°F	Better	High coat-weight, high performance bonding and mounting between irregular and LSE substrates.	80# white SCK	General purpose mounting application. Moderate to High shear mounting	2133			FT1800	
	<b>IM2908</b>	2.0/2.0	1/32" black PE foam	54"x216' 1" x 5'	140	***	***	200°F	Best!	High performance Acrylic Foam Tape	80# white SCK or 5 mil blue HDPE	Soap Dispenser or mirror mounting. High shear mounting	2133				
Acrylic DC	<b>IB2101</b>	1.1/1.1	1/2 mil PET	54"x750' 6" x 30'	486	3.5/3.0	2.4/2.5	250°F	Good	Acrylic double-coat, resistant to plasticizers, high temperatures, and chemicals in a cost effective coat weight	60# white SCK	Cost effective bonding, mounting, nameplates, faceplates, decorative trim, PET Urethane, Polyether, PVC Foam	FT-A	909		M1521	
	<b>IB2130</b>	1.5/1.8	1/2 mil PET	54"x750' 6" x 30'	486	4.5/4.5	6.5/6.5	250°F	Best!	Modified-Acrylic, excellent temperature resistance, tack, peel and shear on a wide variety of substrates	74# white SCK	For High-Tack, High-Temperature application, gasket, seals, automotive, appliance.		9828PC	256M	M1523	
Acrylic FF	<b>IF2012A</b>	2 mil	None	54"x 540 6" x 30'	350	4.1	4	250°F	Good	UL rated, high performance acrylic, 2 MIL, high shear with UV and temperature resistance	83# Brown PCK	Cost effective acrylic bonding applications, nameplates, faceplates, gaskets, foams	Discontinued 8306	467MP/ 467MPF/ 467MPR	7332	TF1552	tesa-4900 Scapa- 120, 310, 420
	<b>IF2015A</b>	5 mil	None	54"x 540 6" x 30'	350	5	5.5	250°F	Best!	UL rated, high performance acrylic, 5 MIL, high shear with UV and temperature resistance	83# Brown PCK	High performance acrylic bonding applications, nameplates, faceplates, gaskets, foams	Discontinued 1125HLP	468MP/ 468MPF/ 468MPR	7335	TF1555	tesa-4988 Scapa- 150, 350, 450
LSE Acrylic FF	<b>IF2092</b>	2 mil	None	54"x 540 6" x 30'	350	7	7	250°F	Good	2 Mil High performance acrylic freefilm, LSE	74# white PCK	LSE PP, PE, Powder-coated paints, aggressive peel and tack	Discontinued 1192	9471LE			Scapa UB2070
	<b>IF2095</b>	5 mil	None	54"x 540 6" x 30'	350	10	10	250°F	Best!	5 Mil High performance acrylic freefilm, LSE	74# white PCK	Heavy coat-weight LSE PP, PE, Powder-coated paints, aggressive peel and tack	Discontinued 1192	9472LE	7435		Scapa UB5070



## Technical Products

800.328.2619 | [MACtac.americas@bemis.com](mailto:MACtac.americas@bemis.com)

4560 Darrow Road | Stow, OH 44224

MAC4098 (03/08)