Overlaminates

Application Guide













High-quality, cost-effective solutions to conquer your image protection challenges.



Overlaminates

Application Guide

Overlaminates keep graphics looking sharp - from initial application to removal. Mactac overlaminates offer superior protection against scuffing, abrasion, moisture and UV light to protect and seal images from environmental elements, foot traffic and more.

									Applications							Media			
Product Code	Face	Adhesive	Liner	Width	Durability	Slip Resistance	Indoor	Outdoor	Full/Partial Fleet Wraps	Full/Partial Vehicle Wraps	Windows	POP/Indoor	Walls	Gruv GVC929 v2	Gruv GV729	Rebel RB500 & RB400 Series	Roughrap RR100		
rayzor																			
LF3640	1.5 Optically Clear Gloss	Permanent	1.2 mil PET	54"	5 years						_								
LF3640G	1.5 Clear Gloss	Permanent	50# G	54"	5 years		-	_			_					•			
LF3630G	1.5 Matte	Permanent	50# G	54", 60"	5 years						-		-						

PET - Polyester G - Bleached glassine

Floor preparation is critical to a successful installation. Please refer to Mactac's Technical Assistance Guide TA2040 "Choosing the Right Floor Graphic Media" for detailed application instructions at www.mactac.com.

								Applications							Media					
Product Code		Face	Adhesive	Liner	Width	Indoor/Outdoor Floor Durability	Slip Resistance	Indoor	Outdoor	Windows	Floors	POP/Indoor	Tradeshows	Wall	Printvinyl PV300, PV500 & PVG300, PVG500	Rebel RB500 & RB400 Series	Rebel RB200 Series	Streetrap STR328		
colorgard luv																				
8000	3.0 mil	Gloss PVC	Permanent	58# WK	54", 60"	5 years			-	_		-	_	_						
8200	3.0 mil	Matte PVC	Permanent	58# WK	54", 60"	5 years			_			-								
8300	3.0 mil	Luster PVC	Permanent	58# WK	54", 60"	5 years			_	_		_								
promogard°																				
PG7000	3.5 mil	Gloss PVC	Permanent	40# WK	54", 60"	4 years			-	_		-		_						
PG7200	3.0 mil	Matte PVC	Permanent	40# WK	54"	4 years			_	_		-	_	_						
PG7200	3.0 mil	Luster PVC	Permanent	40# WK	54"	4 years			_			-								
colorga	rd°floo	or																		
PF6300	5.0 mil	Textured Vinyl	Clear Acrylic Permanent	83# Paper	41", 54"	4 years			_			-		_		П				
PF6400	3.75 mil	Textured Polyolefin	Clear Acrylic Permanent	1.2 mil PET	54"	1 month						-				П				
PF6500C	5.0 mil	Textured Vinyl	Clear Acrylic Permanent	1.2 mil PET	54"	Up to 1 year						-								
PF6600	6.0 mil	Textured Vinyl NFSI HIGH-TRACTION	Clear Acrylic Permanent	78# WK	54"	Up to 1 year	Indoor & Outdoor ANSI/NFSI B101.3, Wet or Dry Conditions~		-			-		_	•	•		•		
SAG 38	1.5 mil	High Gloss PET	Optically Clear Acrylic Permanent	1.7 mil PET	54"	2 years			-	-	-	-		-		П	۵			
SAG 53	2.0 mil	High Gloss, Hard Coated PET	Optically Clear Acrylic Permanent	1.2 mil PET	54"	2 years			_	_	_	-								

ASTM C-1028 Test method formerly withdrawn. No new safety specifications for dry floors has been approved by recognized laboratories. ~ See Performance Guides for more details on product slip resistance.

PET - Polyester WK- White kraft















Open Image WarrantySM for Mactac[®] Media and Laminates:

You make the choice of printer and ink that are best for your business and Mactac will be the partner that stands behind you. Simply provide us with your system and if we have not already tested the combination, we'll run a comprehensive series of tests to ensure the system works and then warrant your application. If we find the components are not compatible we'll let you know that, too, and make alternative recommendations. It's that simple!

We stand behind you. And, we work with the most popular printer and ink suppliers to ensure product compatibility and durability.

