

# Floors

## Application Guide



*Transform high quality images into high-impact floor and sidewalk graphics*

# Floors

## Application Guide

### Overlaminates

Overlaminates keep floor graphics looking sharp – from initial application to removal. Offering superior protection against scuffing, abrasion, moisture and UV light, Colorgard® floor overlaminate products protect and seal images from environmental elements, foot traffic and more. These overlaminates are specially engineered for use with pressure-sensitive floor graphic films and meet or exceed various public safety requirements and industry standards for high traction.

Product Code	Face	Adhesive	Liner	Width	Durability <sup>^</sup>	Slip Resistance	Floor Applications							Floor Media						
							Indoor	Outdoor	Digital Images	POP	Posters	Tradeshows Graphics	High Foot Traffic	Wall Murals	Gruv 400 & 500	Rebel 500	Rebel 200	Streetrap STR328	PVG/PV 300 series	PVG/PV 500 series
<b>colorgard® floor</b>																				
PF6300	Textured Vinyl	Clear Acrylic	83# Paper	54"		Dry Conditions Only	<input type="checkbox"/>													
PF6400	Textured Polyolefin	Clear Acrylic	1.2 mil PET	54"		Dry Conditions Only	<input type="checkbox"/>													
PF6500C	Textured Vinyl	Clear Acrylic Permanent	1.2 mil PET	54"			<input type="checkbox"/>													
<b>colorgard® floor</b>																				
PF6600	Textured Vinyl 	Clear Acrylic	78# WK	54"		Indoor & Outdoor ANSI/NFSI B101.3, Wet or Dry Conditions <sup>~</sup>	<input type="checkbox"/>													

ASTM C-1028 Test method formerly withdrawn. No new safety specifications for dry floors has been approved by recognized laboratories.  
~ See Performance Guides for more details on product slip resistance.

LFP - Layflat polycoated  
SFC - Superflat coated  
WK- White kraft

CCK- Clay coated kraft  
PET - Polyester

**Floor preparation is critical to a successful installation.** Please refer to Mactac's Technical Assistance Guide TA2040 "Choosing the Right Floor Graphic Media" for detailed application instructions at [www.mactac.com](http://www.mactac.com).



## Floor Media

Designed for indoor or outdoor applications, Mactac line of wide-format, digital media is your best choice for high-quality, high-impact floor graphics. With application versatility - from convention centers and retail graphics to sports arenas and sidewalks - these printer-friendly floor graphic vinyls produce images that impress. Offering various options in thickness, finish and adhesive aggressiveness and strengths, Mactac vinyls and films offer the flexibility you need for any floor graphic application you encounter.

Product Code	Face	Adhesive	Liner	Width	Durability <sup>^</sup>	Removability	Floor Applications								Overlaminates				
							Indoor	Outdoor	Labels/Decals/Marking	POP	Signage/Displays	Posters	Low Pile Carpet	Smooth Floor / Tile	Unsealed Rough Concrete/Asphalt	Colorgard PF6300	Colorgard PF6400	Colorgard PF6500	Colorgard PF6600
<b>rebel<sup>®</sup></b>																			
RB528R	4.0 mil Matte White Vinyl	Removable Clear Acrylic	90# LFP	54", 60"	5 years	Up to 1 year	■	■	■	■	■	■	■	■	■	■	■	■	■
RB529R	4.0 mil Gloss White Vinyl	Removable Clear Acrylic	90# LFP	54", 60"	5 years	Up to 1 year	■	■	■	■	■	■	■	■	■	■	■	■	■
RB599R	4.0 mil Gloss Clear Vinyl	Removable Clear Acrylic	90# SFC	54"	5 years	Up to 1 year	■	■	■	■	■	■	■	■	■	■	■	■	■
<b>printvinyl<sup>™</sup></b>																			
PV328R	3.2 mil Matte White Vinyl	Removable Clear Acrylic	78# CCK	54"	3 years	Up to 2 years	■	■	■	■	■	■	■	■	■	■	■	■	■
PV529R	3.5 mil Gloss White Vinyl	Removable Clear Acrylic	90# LFP	54"	5 years	Up to 2 years	■	■	■	■	■	■	■	■	■	■	■	■	■
<b>printvinyl<sup>™</sup>gray</b>																			
PVG528R	3.8 mil Matte White Vinyl	Removable Gray Opaque Acrylic	86# Kraft	54"	5 years	Up to 2 years	■	■	■	■	■	■	■	■	■	■	■	■	■
PVG528HT	3.2 mil Matte White Vinyl	High-tack Opaque Acrylic	90# LFP	54"	5 years	Up to 6 months	■	■	■	■	■	■	■	■	■	■	■	■	■
<b>streetrap<sup>®</sup></b>																			
STR328	4.0 mil Matte White Vinyl	Aggressive Permanent Opaque	90# SFC	54"	Up to 1 year	3 months**	■	■	■	■	■	■	■	■	■	■	■	■	■

\* Do not apply Streetrap to smooth, sealed concrete, unless a permanent bond is desired.

\*\* See Performance Guide for Removal Instruction off unsealed concrete only

^ 1 Month up to 1 year for pedestrian traffic and maybe up to 1 week for light vehicular traffic on smooth to slightly rough surfaces



# Floors

## Application Guide

### **Open Image Warranty<sup>SM</sup> for Mactac<sup>®</sup> Media and Laminates:**

You make the choice of printer and ink that are best for your business and Mactac will be the partner that stands behind you. Simply provide us with your system and if we have not already tested the combination, we'll run a comprehensive series of tests to ensure the system works and then warrant your application. If we find the components are not compatible we'll let you know that, too, and make alternative recommendations. It's that simple!

We stand behind you. And, we work with the most popular printer and ink suppliers to ensure product compatibility and durability.

