Macbond® Foam Bonding Tapes

Engineered Tapes & Laminates



















Differential tape series that blends the foam bonding performance of FBR899 (unwind side) with the high performance of XT (liner side) for bonding to smooth surfaces and low surface energy materials.





Seals



Macbond® Foam Bonding Tapes


Engineered Tapes & Laminates

Features

- Differential tape series that blends the foam bonding performance of FBR899 with the high shear performance of XT Rubber.
- 0.5 mil PET Carrier for dimensional stability
- 60# SCK and 80# SCK Liner options available

Benefits

- FBR899 is an versatile adhesive, bonding well to open and closed cell foams, textiles and textured surfaces.
- XT Rubber is a high performance rubber adhesive, with exceptional shear strength. Bonds well to metals, plastics and low surface energy substrates.
- Available in 54" and 60" web widths
- Easy to laminate and die cut



Double Coated Tapes

Construction									Master Roll		MSI	
Part Number	Carrier	Adhesive		Coat Weight Mils		Caliper Mils	1:	End Use	Width	gth	l <	Stock/MTO
		Liner	Unwind	Liner	Unwind	Carrier & Adhesive	Liner	Release	Wie	Len	Weight,	Sto
FBT360W60	.5mil PET	XT Rubber	FBR899	1.2	1.8	3.5	60# White SCK	Medium	60"	750'	0.33	S
FBT360W54	.5mil PET	XT Rubber	FBR899	1.2	1.8	3.5	60# White SCK	Medium	54"	750'	0.33	S
FBT380W60	.5mil PET	XT Rubber	FBR899	1.2	1.8	3.5	80# White SCK	Medium	60"	750'	0.34	S
FBT380W54	.5mil PET	XT Rubber	FBR899	1.2	1.8	3.5	80# White SCK	Medium	54"	750'	0.34	S

For additional Performance Guides on Macbond Ultra 555 products, please visit www.mactac.com.

Mactac is ISO9000-2015 certified.

Mactac is a member of the following organizations:

Gasket Fabricators Association

National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)

Pressure Sensitive Tape Council (PSTC)

