



PERFORMANCE GUIDE

Represents Typical Values Only

www.Mactac.com

JCP9501

Clear Polypropylene Ink Jet -

Revised: 10/2017 CCF

Description	Applications and End Uses		
Product	JCP9501 is a glossy, clear ink jet BOPP film with a permanent acrylic based adhesive with a 2.45 mil semi-bleached calendar kraft liner. Roll-to-roll applications, not run to Layflat.		
Face	A glossy, transparent ink jet printable polypropylene with good water resistance. Compatible with water based inks (Dye & Pigmented) – please test for suitability.		
	Physical Properties Without Adhesive		
	Caliper, inches	0.0032+/- 10%	TAPPI T-411
	Transparency	92% Min	ISO2471
	Tensile, kg Min	TBD	TAPPI T-494
	Tear, kg Min	TBD	TAPPI T-414
	Basis Weight, lbs. (25" x 38"/500)	53.1 +/- 10%	TAPPI T-410
Adhesive	ST95 is a permanent acrylic emulsion with aggressive initial tack, excellent ultimate adhesion and mandrel hold. Very good adhesion to corrugated, glass, and various plastic substrates. Considered to be latex glove friendly for use in some healthcare applications.		
	Physical Properties of Adhesive		
	Thickness, inches	0.0007 +/- 10%	
	Peel Adhesion, lbs./in.	2.6	PSTC-101A (30 min. applied stainless steel)
	Temperature Ranges		
	Minimum Application	+25°F (-4°C)	
	Service Ranges	-75°F to +200°F (-59°C to +93°C)	
Liner	A semi-bleached calendar kraft liner excellent for die cutting, stripping and label dispensing. Primarily for roll -to -roll applications.		
	Caliper, inches	0.00245 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	40 +/- 10%	TAPPI T-410
Shelf Life	One year when stored at 72° F and 50% R.H.		

The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances, please contact your Mactac sales representative to discuss your requirements for recommendations. If this is a printed Performance Guide, it is an uncontrolled document. Please check the Mactac website for the latest, most up-to-date version at www.mactac.com

Note: JCP9501 ink jet is designed to run smoothly in a variety of ink jet printers. Mactac highly recommends sufficient testing on the material in its intended design prior to use.

CALL 1-800-548-3456 for additional product information

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

