



PERFORMANCE GUIDE

Represents Typical Values Only

www.Mactac.com

PTC8891-0

Revised: 07/2014 KSH

2 mil Clear Polypropylene / MP880 / 1 mil PET liner

Description	Applications and End Uses		
Product	PTC8891-0 is a 2.0 mil clear top coated Polypropylene film featuring MP880, an acrylic adhesive designed for prime film labeling and a 1 mil PET liner.		
	Label applications requiring a semi-conformable, clear, "No Label Look" film for food, cosmetic, beverage, and household cleaner market segments. Excellent flexo and thermal transfer printability.		
Face	A 2 mil clear, top coated, biaxially oriented polypropylene (BOPP) film designed for applications where ultra clarity is needed for a "no label" look. Proprietary top coating delivers excellent adhesion for superior graphics and print receptivity for various methods including: UV Flexo, Water Flexo, Gravure, UV Inkjet, Hot Stamp and Thermal Transfer. Great stiffness for efficient dispensability.		
	Physical Properties Without Adhesive		
	Caliper, inches	0.002 (2.0 mil)	ASTM D2103
	Gloss % Reflectance at 45° angle	85	ASTM D2547
	Haze	2.5	ASTM D1003
	Tensile, lbs./in.	20 MD 35 CD	ASTM D882
	Elongation, %	180 MD 55 CD	ASTM D882
Adhesive	MACtac MP-880 is a permanent acrylic adhesive with excellent tack and ultimate adhesion to a variety of surfaces. MP-880 is designed for film and paper labeling applications. It exhibits good clarity, resistance to water whitening, and some open time (please test for suitability).		
	Physical Properties of Adhesive		
	Thickness, inches	0.0008 +/- 10%	
	180° Peel Adhesion, lbs./in.		CTM-8 (30 min. applied) Reference: PSTC-101A
		HDPE: 1.0	
		Stainless Steel: 2.2	
		PP: 1.0	
		Glass: 2.3	
		PET: 2.4	
	Loop Tack (1"), lbs./in.		CTM-25
		HDPE: 1.3	
		Stainless Steel: 2.7	
		PP: 1.0	
		Glass: 3.4	
		PET: 3.1	
	Temperature Ranges		
	Minimum Application	+40°F (4°C)	CTM #45 Curwood
	Service Ranges	-65°F to +350°F (-54°C to +176°C)	Polyester Film Dry Surface
Liner	A 1 mil clear polyester liner excellent for die cutting, stripping and label dispensing. Primarily for roll-to-roll applications. Specifically designed for use with clear film face materials or applications requiring excellent clarity.		
	Caliper, inches	0.00092 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	19.8 +/- 10%	TAPPI T-410
Shelf Life	One year when stored at 72° F and 50% R.H.		

This product complies with CONEG regulations. All Mactac Roll Label products meet the requirements of the Clean Air Act of 1990.

CALL 1-800-548-3456 for additional product information

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

© Registered Trademark of Morgan Adhesives Company.

