

PERFORMANCE GUIDE

Represents Typical Values Only

www.mactac.com

PTS8891-2 Revised: 07/2019 RDF

2.0 mil Chrome Polypropylene / MP880 / 1.2 mil PET

Description	PTS8891-2 is a 2.0 mil chrome top coated Polypropylene film featuring MP-880, an acrylic adhesive designed for prime film labeling and a 1.2 mil PET liner.		Applications and End Uses Label applications requiring a semi- conformable film for food, cosmetic, beverage, and household cleaner market segments.		
Product					
Face	A 2.0 mil chrome, top coated, biaxially oriented polypropylene (BOPP) film designed for excellent printing, converting and label dispensing. Proprietary top coating delivers excellent adhesion for superior graphics and print receptivity for various methods including UV Flexo, Water-based Flexo, Gravure, Screen and Offset.				
	Physical Properties Without Adh	esive			
	Caliper, inches		0.002 (2.0 n	nil)	ASTM 313E
	Tensile, lbs./in.		58 MD 52	CD	ASTM D882
	Elongation at break, %		105 MD		ASTM D882
Adhesive	MP-880 is a permanent acrylic adhesive with excellent tack and ultimate adhesion to a variety of surfaces. MP-880 is designed for film and paper labeling applications. It exhibits good clarity, resistance to water whitening, and some open time (please test for suitability).				
	Physical Properties of Adhesive	0.0000 . / 400/			
	Thickness, inches	0.0008 +/- 10%		DCTC 10	11.4
	180° Peel Adhesion, lbs			PSTC-10	JIA
		HDPE: 1.0 Stainless Steel: 2.2			
		PP: 1.0			
		Glass: 2.3			
		PET: 2.4			
	Loop Tack (1"), lbs./in.	161. 2.4		PSTC-16	•
	2000 1001 (1), 1001, 111	HDPE: 1.3			•
		Stainless Steel: 2.7			
		PP: 1.0			
		Glass: 3.4			
		PET: 3.1			
	Temperature Ranges				
	Minimum Application +40°F (4°C) Service Ranges -65°F to + 350°F (-54°C)		C to +176°C)	CTM #45 Curwood Polyester Film Dry Surface	
Liner	A 1.2 mil clear polyester liner excellent for die cutting, stripping and label dispensing. Primarily for roll-to-roll applications.				
	Caliper, inches		0.0012 +/- 10%		TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)		26 +/- 10%		TAPPI T-410
Shelf Life	One year when stored at 72° F and 50% R.H.				

This product complies with CONEG regulations. All MACtac Roll Label products meet the requirements of the Clean Air Act of 1990.

Note: The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances, please contact your MACtac sales representative to discuss your requirements for recommendations. If this is a printed Performance Guide, it is an uncontrolled document. Please check the MACtac website for the latest, most up-to-date version at www.mactac.com

IMPORTANT NOTICE: The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

 $^{\text{TM}}$ Trademark of Morgan Adhesives Company.



[®] Registered Trademark of Morgan Adhesives Company.