

## VCL0034

Revised: 06/2016 KSH

## 6 mil Top-coated Static Cling Vinyl / 60# Liner

Description		Applications and End Uses	
Product	6.0 mil white gloss top-coated flexible static cling vinyl (no adhesive needed) and a 60 lb. liner. This product is ideal for promotional window graphics and automotive oil change decals.	This product is a self-clinging film, which requires no adhesive, applies quickly to most smooth polished surfaces and is easily removed. Some of the many uses include window advertising, POP window decals, price stickers, automotive window decals and reusable seasonal decals.	
Face	The face film is a white high gloss top-coated highly plasticized polyvinyl chloride (PVC) flexible static cling vinyl film which adheres to most clean, high polished, smooth surfaces. Excellent chemical resistance (commercial window cleaners, etc.). Printable with water based flexo, UV flexo, thermal transfer and screen inks.		
	Physical Properties Without Adhesive		
	Caliper, in	0.006	ASTM D2103
	Surface Tension	32 dynes	
	Temperature Ranges		
	Minimum Application Service Ranges	+40°F -10°F to +150°F	CTM #45 Curwood Polyester Film Dry Surface
Adhesion	Excellent, non-top coated side of the vinyl will adhere to glass and other highly polished surfaces. It is recommended not to apply the top-coated or printed side to glass as the ink may transfer to the glass upon removal of the film.		
Liner	A 60 Lb. liner for ease of handling and die cutting.		
	Caliper, inches	0.0035 +/- 10%	TAPPI T-411
Durability	Two years (interior of window glass). Up to 6 months from time of application on an outside window. Outdoor climate may limit the bond of static cling vinyl on exterior windows.		
Shelf Life	Six months when stored at 70° F and 50% relative humidity.		

\* Values given are typical for unprocessed product and are not for use as specifications. Processing may change the values.

**CALL 1-800-548-3456 for additional product information**

**IMPORTANT NOTICE:** The information given, and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

[www.Mactac.com](http://www.Mactac.com)

