



Starliner Label Products

Revised 04/10

Badge Label

Description		Applications and End Uses		
Laser printable paper with badge adhesive and lay flat liner.		Temporary badge or I.D. for meetings, conventions, tradeshow. Laser printable on most desk top and medium speed laser printers.		
Stock Number	Label Size	Sheet Size	Number of Labels	Sheets/ Box
SR6648	2 1/8" x 3 3/8"	8 1/2" x 11"	8	100
Face	A nominal 40# bright white flexible face stock designed for excellent toner anchorage in most desktop toner fusion laser printers and photocopiers.			
	Typical Physical Properties of Face Stock without Adhesive			
	Caliper, inches	0.0034 +/- 10%	TAPPI T-411	
	Brightness	89	TAPPI T-452	
	Tear, grams	34 MD 36 CD	TAPPI T-414	
	Tensile, lbs./in.	19 MD 9.5 CD	TAPPI T-494	
	Smoothness, Sheffield Units	125	TAPPI T-538	
	Basis Weight, lbs. (25" x 38"/500 sheets)	41 +/- 10%	TAPPI T-410	
Adhesive	Specifically designed for up to 24 hours use on fabric. It exhibits good holding power on fabric and removes cleanly and is non-staining. CAUTION: Not recommended for use on fur, leather, and suede, sequins, corduroy or silk. This is a permanent type adhesive and should not be used where long term removability is required such as sock and tights bands or size labels.			
	Typical Physical Properties of Adhesive			
	Thickness, inches	0.0006 +/- 10%	TAPPI T-411	
	Peel Adhesion, lbs./in.	1.0	PSTC-2 (30 min. applied)	
	Temperature Ranges			
	Minimum Application	+35°F (4°C)	CTM #45 Curwood	
	Service Ranges	-60°F to +200°F (-51°C to +93°C)	Polyester Film Dry Surface	
Liner	A nominal 40# white Kraft liner has excellent lay-flat characteristics and flexibility for most desktop laser printers.			
	Typical Physical Properties of Liner			
	Caliper, inches	0.0025 +/- 10%	TAPPI T-411	
	Basis Weight, lbs. (24" x 36"/500 sheets)	40 +/- 10%	TAPPI T-410	

Total Caliper (± 10%)	Inches	Mils (0.001 inch)	Grams Meter Square	Micron s
	0.0064 "	6.4 mils	145 g/m ²	163 μ
Printing Process	Desktop laser printing. Desktop ink jet and free standing laser / copiers. Always test and follow printer manufacturer's recommendations.			
Shelf Life	One year when stored at 72° F and 50% R.H.			

** Values given are typical for unprocessed product and are not for use as specifications. Processing may change the values.*

CALL 1-800-321-8834 for additional product information

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

www.Mactac.com

