



Starliner[®]

Cinema[®] 60# Cast Coated High Gloss - *Removable*

Stock Numbers	Sheet Size	Sheet Size	Sheet Size
SL 0041	8 1/2" x 11"	SL 0005	17" x 22"
		SL 0016	26" x 20"

Construction

Face: 60# Cast Coated Gloss
Adhesive: MR810 Removable Acrylic
Liner: Specially processed scored release liner. Back printed in blue "Starliner Removable".

Applications and End Uses

Labels, promotions and POP requiring a high gloss appearance with a removable adhesive.

Description

Face A 60# white gloss, cast-coated litho. Provides a rich, lustrous, mirror finish for superior detail printing.

Typical Physical Properties of Face Stock without Adhesive

Caliper, inches	0.0040 +/- 10%	TAPPI T-411
Brightness %	86	TAPPI T-452
Gloss % Reflectance at 75° angle	90	TAPPI T-480
Opacity %	90	TAPPI -425
Tear, grams.	25 MD 30 CD	TAPPI T-414
Tensile, lbs./in.	35 MD 15 CD	TAPPI T-494
Basis Weight, lbs. (25" x 38"/500 sheets)	60+/- 10%	TAPPI T-410

Adhesive

MR-810 is a general purpose, REMOVABLE, acrylic adhesive characterized by moderate tack and bond to a wide variety of surfaces. The adhesive exhibits clean removability from most surfaces and is specifically formulated to all but eliminate sheet-edge adhesive bleed problems. Always pretest removable adhesives for suitability in each particular end use application.

Typical Physical Properties of Adhesive

Thickness, inches	0.0007 +/- 10%	TAPPI T-411
Peel Adhesion, lbs./in.	1.0	PSTC-2 (30 min. applied)
Minimum Application Temperature	+35°F (-2°C)	CTM #45 Curwood
Service Ranges	-65°F to +200°F (-54°C to +93°C)	Polyester Film Dry Surface

Liner

A nominal 80# white kraft liner with scores every 1 1/4", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.

Typical Physical Properties of Liner

Caliper, inches	0.0042 +/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410

Total Caliper 0.0088 ± 10% inches (8.8 mils)

Printing Process Printable by offset-lithography with compatible ink systems.

Shelf Life One year when stored at 70° F and 50% R.H.

This product complies with CONEG regulations.

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

www.Mactac.com

