



Starliner[®]

60# Fluorescents – **Permanent**

Stock Numbers			Sheet Size			Sheet Size
	Burlesque Red	SL 2211	8 ½" x 11"	Limelite Chartreuse	SL 2238	8 ½" x 11"
Burlesque Red	SL 2212	17" x 22"	Limelite Chartreuse	SL 2215	17" x 22"	
Marquee Green	SL 2218	8 ½" x 11"	Passion Pink	SL 2239	8 ½" x 11"	
Marquee Green	SL 2213	17" x 22"	Passion Pink	SL 2216	17" x 22"	
Vaudeville Orange	SL 2237	8 ½" x 11"				
Vaudeville Orange	SL 2214	17" x 22"				

Construction

Face: 60# Fluorescent Colors
Adhesive: Permanent Acrylic
Liner: Specially processed scored release liner. Back printed in red "Starliner Permanent".

Applications and End Uses

Labels, inventory, shipping, warning labels and POP requiring a bright intense attention getting appearance. Laser / Digital compatible. Always test and follow printer manufacturer's instructions regarding the use of pressure media.

Description

Face A 60# matte coated fluorescent litho in a variety of bold, intense colors for attention getting impact.

Typical Physical Properties of Face Stock without Adhesive

Caliper, inches	0.0045 (4.5 mils) ± 10%	TAPPI T-411
Tear, grams.	60 MD 70 CD	TAPPI T-414
Tensile, lbs./in.	34 MD 14 CD	TAPPI T-494
Basis Weight, lbs. (25" x 38"/500 sheets)	60+/- 10%	TAPPI T-410

Adhesive

An acrylic emulsion with aggressive initial tack and excellent ultimate adhesion to corrugated, glass, fiber drums and various plastic substrates and other common substrates. Its patented non-ooze characteristics will provide clean kiss, die, and guillotine cutting.

Typical Physical Properties of Adhesive

Thickness, inches	0.0007 +/- 10%	TAPPI T-411
Peel Adhesion, lbs./in.	3.0	PSTC-2 (30 min. applied)
Temperature Ranges		
Minimum Application	+35°F (-2°C)	CTM #45 Curwood
Service Ranges	-65°F to +200°F (-54°C to +93°C)	Polyester Film Dry Surface

Liner

A nominal 80# white kraft liner with scores every 1 ¼", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.

Typical Physical Properties of Liner

Caliper, inches	0.0042 +/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410

Total Caliper

0.0094 ± 10% inches (9.4 mils)

Printing Process

Printable by offset-lithography with compatible ink systems. Laser compatible with production sized toner fusion printers capable of using heavier weight materials. Use laser compatible inks if pre-printing. Follow printer manufacturer's recommendations on printing pressure sensitive media and always test.

Shelf Life

Two years when stored at 70° F and 50% R.H.

This product complies with CONEG regulations.

For ordering and product information call 1-800-321-8834

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

[®] Registered Trademark of Morgan Adhesives Company.

