

www.Mactac.com



Updated 07/11

## Prestige ITC White White Vinyl - **Ultra Removable** for Indigo Printing

Certified for HP Indigo  
5000/5500 & 7000/7500  
Presses by Rochester  
Institute of Technology



Stock Number	Sheet Size	Sheets /Carton
INV8200	12" x 18"	100

  

Construction		Applications and End Uses	
<b>Face:</b>	White Vinyl Topcoated for sheet fed HP Indigo	Sheet fed HP Indigo presses. Use for POP, bumper sticker, cooler displays, window displays, and menu boards.	
<b>Adhesive:</b>	Ultra Removable		
<b>Liner:</b>	Specially processed scored release liner.		

  

Face	Base face stock is a 3.5 mil white matte calendared vinyl. This durable, flexible, vinyl conforms well to irregular surfaces.		
	<b>Typical Physical Properties of Face Stock with Adhesive</b>		
<b>Caliper</b> , inches	0.0035 ± (3.5 mils)	TAPPI T-411	
<b>Brightness</b>	37.5	TAPPI T-480	
<b>Gloss</b>	83%	TAPPI T-452	

  

Adhesive	An ultra removable acrylic adhesive removes cleanly up to 6 months from most flat surfaces such as glass, painted walls, painted metal, hard plastics. Recommend testing for intended use.		
	<b>Typical Physical Properties of Adhesive</b>		
Temperature Ranges			
Minimum Application	+45°F (7°C)	CTM #45 Curwood	
Service Ranges	-20°F to +150°F (-29°C to +66°C)	Polyester Film Dry Surface	

  

Liner	A nominal 80# white kraft liner with scores every 1 ¼", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.		
	<b>Typical Physical Properties of Liner</b>		
Caliper, inches	0.0042+/- 10%	TAPPI T-411	
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410	

  

Total Caliper	Typical values +/-10%			
	Inches	Mils (0.001 inch)	Grams Meter Square	Microns
	0.0088"	8.8 mils	267 g/m <sup>2</sup>	223.52μ

  

<b>Printing Process</b>	HP Indigo sheet fed printing
<b>Shelf Life</b>	One year when stored at 70° F and 50% R.H.

This product complies with CONEG regulations

**For ordering and product information call 1-800-548-3456**

**For more application recommendations call 1-800-334-7310**

**IMPORTANT NOTICE:** The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the foregoing provisions unless in a specific agreement signed by the officers of seller and manufacturer. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

[www.Mactac.com](http://www.Mactac.com)

