

www.Mactac.com



Updated 03/13

Lyric[®] ITC
60# Matte Litho - **Permanent** for Indigo Printing

Certified for HP Indigo
5000/5500 & 7000/7500
Presses by Rochester
Institute of Technology



Stock Number	Sheet Size		Sheets/Carton		
	Sheet Size	Sheets/Carton	Sheet Size	Sheets/Carton	
SLI7250	12" x 18"	200	SLI7250-13	13" x 19"	500
SLI7250-5	12" x 18"	500	SLI7250-00*	12" x 18"	200

	Construction	Applications and End Uses
Face:	60# matte coated litho for sheet fed HP Indigo	Sheet fed HP Indigo presses. End uses include point of purchase, decorative labels, calendar markers, corporate ID, signage.
Adhesive:	Permanent Acrylic	
Liner:	Specially processed scored release liner. Back printed in red "Starliner Permanent" * No scores or back print	

Face	A 60# white matte coated litho optimized with proprietary top coating for HP Indigo sheet fed presses.
Typical Physical Properties of Face Stock with Adhesive	
Caliper , inches	0.0040 +/- 10% TAPPI T-411
Brightness	84.25 TAPPI T-452
Basis Weight , lbs. (25" x 38"/500 sheets)	60 +/- 10% TAPPI T-410

Adhesive	Permanent acrylic emulsion adhesive exhibiting a high initial tack on most common substrates. Its patented non-ooze characteristics will provide clean kiss, die, and guillotine cutting.
Typical Physical Properties of Adhesive	
Thickness, inches	0.0006 +/- 10% TAPPI T-411
Photographic Activity Test	Passes ISO 14523
Temperature Ranges	
Minimum Application	+35°F (1.66°C) CTM #45 Curwood
Service Ranges	-65°F to +200°F (-54°C to +93°C) Polyester Film Dry Surface

Liner	A nominal 80# white kraft liner with scores every 1 1/4", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting. Also available without scores.
Typical Physical Properties of Liner	
Caliper, inches	0.0042 +/- 10% TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10% TAPPI T-410

Total Caliper	Typical values +/-10%			
	Inches	Mils (0.001 inch)	Grams Meter Square	Microns
	0.0088"	8.8 mils	236 g/m ²	223.5 μ

Printing Process	HP Indigo sheet fed printing
Shelf Life	Two years when stored at 70° F and 50% R.H.

This product complies with CONEG regulations

For ordering and product information call 1-800-321-8834

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

