

www.Mactac.com



Updated 07/11

Matinee[®] ITC
60# Semi Gloss - **Permanent** for Indigo Printing

Certified for HP Indigo 5000/5500 & 7000/7500 Presses by Rochester Institute of Technology



Stock Number		Sheet Size	Sheets/Ctn		Sheet Size	Sheets/Ctn
	SLI7210	12" x 18"	200	SLI7210-13	13" x 19"	500
	SLI7210-5	12" x 18"	500	SLI7210-00*	12" x 18"	200

Construction

Face: 60# coated one side semi gloss for sheet fed HP Indigo
Adhesive: Permanent Acrylic
Liner: Specially processed scored release liner. Back printed in red "Starliner Permanent"
 * No scores or back print

Applications and End Uses

Sheet fed HP Indigo presses. End uses include point of purchase, decorative labels, calendar markers, corporate ID, signage.

Face A coated one sided semi gloss optimized with proprietary top coating for HP Indigo sheet fed presses.

Typical Physical Properties of Face Stock with Adhesive

Caliper , inches	0.0031 +/- 10%	TAPPI T-411
Brightness	83.7	TAPPI T-452
Gloss	74.3	TAPPI T-480
Opacity	88	TAPPI T-452
Basis Weight , lbs. (25" x 38"/500 sheets)	60 +/- 10%	TAPPI T-410

Adhesive Permanent acrylic emulsion adhesive exhibiting a high initial tack on most common substrates. Its patented non-ooze characteristics will provide clean kiss, die, and guillotine cutting.

Typical Physical Properties of Adhesive

Thickness, inches	0.0006 +/- 10%	TAPPI T-411
Photographic Activity Test	Passes	ISO 14523
Temperature Ranges		
Minimum Application	+35°F (1.66°C)	CTM #45 Curwood
Service Ranges	-65°F to +200°F (-54°C to +93°C)	Polyester Film Dry Surface

Liner A nominal 80# white kraft liner with scores every 1 1/4", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting. Also available without scores.

Typical Physical Properties of Liner

Caliper, inches	0.0042 +/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410

Total Caliper

Typical values +/-10%	Inches	Mils (0.001 inch)	Grams Meter Square	Microns
	0.0079"	7.9 mils	224 g/m ²	200.66 μ

Printing Process HP Indigo sheet fed printing

Shelf Life Two years when stored at 70° F and 50% R.H.

For ordering and product information call 1-800-321-8834



PERFORMANCE GUIDE

www.Mactac.com

This product complies with CONEG regulations

*For ordering and product information call **1-800-321-8834***

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

