



## Metro Digital

Update  
d 10/14

### White Vinyl Ultra Removable for Indigo

		Sheet	Sheets /	Liner Description
<b>Stock Numbers</b>	MIV1218WUS-1	12" x 18"	100	Scores every 1 ¼"
	MIV1319WUS-1	13" x 19"	100	Scores every 1 ¼"

#### Construction

<b>Face:</b>	White Vinyl for commercial HP Indigo presses
<b>Adhesive:</b>	Ultra removable acrylic adhesive
<b>Liner:</b>	Lay flat liner

#### Description

<b>Face</b>	Matte white vinyl optimized for sheet fed HP Indigo presses		
	<b>Typical Physical Properties of Face Stock without Adhesive</b>		
	Caliper, inches	0.0034 +/- 10%	TAPPI T-411
<b>Adhesive</b>	An ultra-removable acrylic adhesive removes cleanly up to 6 months from most flat surfaces such as glass, painted walls, painted metal, hard plastics. Recommend testing		
	<b>Typical Physical Properties of Adhesive</b>		
	Temperature Ranges		
	Minimum Application	+45°F (7°C)	CTM #45 Curwood
	Service Ranges	-20°F to +150°F (-29°C to +66°C)	Polyester Film Dry Surface
<b>Liner</b>	A cost effective white kraft liner has outstanding lay-flat characteristics and internal strength. toughness. tear resistance for kiss cutting.		
	<b>Typical Physical Properties of Liner</b>		
	Caliper, inches	0.0042 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410
<b>Total Caliper</b>	0.0088 ± 10% inches (8.8 mils)		
<b>GSM</b>	268 ± 10%		
<b>Printing Process</b>	Sheet fed commercial toner HP Indigo presses		
<b>Shelf Life</b>	One year when stored at 72° F and 50% R.H.		

This product complies with CONEG regulations.

**IMPORTANT NOTICE:** The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

[www.Mactac.com](http://www.Mactac.com)

