



Metro

Updated 10/13

Color Offset

Stock Numbers	Color	Sheet Size	Color	Sheet Size	
NY2051	Red Offset	8½" x 11"	NY2056	Orange Offset	17" x 22"
NY2052	Red Offset	17" x 22"	NY2057	Blue Offset	8½" x 11"
NY2053	Yellow	8½" x 11"	NY2058	Blue Offset	17" x 22"
NY2054	Yellow	17" x 22"	NY2059	Green Offset	8½" x 11"
NY2055	Orange	8½" x 11"	NY2060	Green Offset	17" x 22"

Construction

- Face:** Color Offset
- Adhesive:** General purpose permanent acrylic adhesive
- Liner:** Scored release liner, no printing on liner

Description

Face	An economical colored offset sheets available in several colors		
	Typical Physical Properties of Face Stock without Adhesive		
	Caliper, inches	0.0052 +/- 10%	TAPPI T-411
	Tear, grams	65 MD 70 CD	TAPPI T-414
	Tensile, lbs./in.	26 MD 13 CD	TAPPI T-494
	Basis Weight, lbs. (25" x 38"/500 sheets)	60+/- 10%	TAPPI T-410
Adhesive	General Purpose Permanent bonds well to a wide variety of surfaces.		
	Typical Physical Properties of Adhesive		
	Thickness, inches	0.0007 +/- 10%	
	Peel Adhesion, lbs./in.	2.0	PSTC-2 (30 min. applied)
	Temperature Ranges		
	Minimum Application	+35°F (1.6°C)	CTM #45 Curwood Polyester Film Dry Surface
	Service Ranges	-65°F to +180°F (-54°C to +82°C)	
Liner	A cost effective white kraft liner with scores every 1 ¼", has outstanding lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.		
	Typical Physical Properties of Liner		
	Caliper, inches	0.0042 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410
Total Caliper	0.0101 ± 10% inches (10.1mils)		
Printing Process	Printable by offset-lithography and screen-printing process with ink systems compatible with this product. Laser compatible with production sized toner fusion printers capable of using heavier weight materials. Use laser compatible inks if pre-printing. Follow printer manufacturer's recommendations on printing pressure sensitive media and always test.		
Shelf Life	Two years when stored at 72° F and 50% R.H.		

This product complies with CONEG regulations.

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC
www.Mactac.com

