



## Metro

Updated 12/16

## Coated Matte Litho

		Sheet Size	Sheets / CTN	Liner Description
<b>Stock Numbers</b>	NY2006R	8.5" x 11"	2000	Standard Scores, no printing on liner
	NY2007R	17.25" x 22.25"	500	Standard Scores, no printing on liner
	NY2008R	26" x 20"	500	Standard Scores, no printing on liner

### Construction

<b>Face:</b>	Matte coated litho
<b>Adhesive:</b>	General purpose removable adhesive
<b>Liner:</b>	Scored release liner with printing on liner.

### Description

<b>Face</b>	An economical matte coated litho sheet		
	<b>Typical Physical Properties of Face Stock without Adhesive</b>		
	Caliper, inches	0.0039 +/- 10%	TAPPI T-411
	Tear, grams	58 MD 63 CD	TAPPI T-414
	Tensile, lbs./in.	36 MD 15 CD	TAPPI T-494
	Basis Weight, lbs. (25" x 38"/500 sheets)	60 +/- 10%	TAPPI T-410

<b>Adhesive</b>	A general purpose removable acrylic adhesive with moderate tack and bond to a wide variety of substrates. The adhesive cleanly removes from most surfaces. Testing is recommended to determine the suitability for specific applications. Always pretest removable adhesives for suitability in each particular end use application.		
	<b>Typical Physical Properties of Adhesive</b>		
	Thickness, inches	0.0007 +/- 10%	
	Peel Adhesion, lbs./in.	1.0	PSTC-2 (30 min. applied)
	Temperature Ranges		
	Minimum Application	+35°F (1.6°C)	CTM #45 Curwood
	Service Ranges	-65°F to +180°F (-54°C to +82°C)	Polyester Film Dry Surface

<b>Liner</b>	A cost effective white kraft liner with scores every 1 ¼", has outstanding lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.		
	<b>Typical Physical Properties of Liner</b>		
	Caliper, inches	0.0042 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410

**Total Caliper** 0.0088 ± 10% inches (8.8 mils)

**Printing Process** Printable by offset-lithography and screen-printing process with ink systems compatible with this product. Laser compatible with production sized toner fusion printers capable of using heavier weight materials. Use laser compatible inks if pre-printing. Follow printer manufacturer's recommendations on printing pressure sensitive media and always test. Guillotine face down with sharp clean blades to avoid adhesive ooze or uneven edges.

**Shelf Life** One year when stored at 72° F and 50% R.H.

This product complies with CONEG regulations.

**IMPORTANT NOTICE:** The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

<sup>®</sup> Registered Trademark of Morgan Adhesives Company.

