



Metro

Updated 10/13

Coated Matte Litho OPAQUE

| | | Sheet Size | |
|----------------------|----------|------------|---------------------------------------|
| Stock Numbers | NY2007OP | 17" x 22" | Standard scores, no printing on liner |
| | NY2008OP | 26" x 20" | Standard scores, no printing on liner |

Construction

| | |
|------------------|--|
| Face: | Matte Coated Litho |
| Adhesive: | General purpose permanent acrylic adhesive |
| Liner: | Scored release liner. |

Description

Face An economical matte coated litho sheet with a with a periwinkle opaque barrier for covering incorrect or outdated information.

Typical Physical Properties of Face Stock without Adhesive

| | | |
|---|---------------|-------------|
| Caliper, inches | 0.0037+/- 10% | TAPPI T-411 |
| Opacity % | 99.5 | TAPPI T-425 |
| Basis Weight, lbs. (25" x 38"/500 sheets) | 60+/- 10% | TAPPI T-410 |

Adhesive General Purpose Permanent bonds well to a wide variety of surfaces. It is especially formulated to all but eliminate sheet edge adhesive bleed.

Typical Physical Properties of Adhesive

| | | |
|-------------------------|----------------------------------|----------------------------|
| Thickness, inches | 0.0007 +/- 10% | |
| Peel Adhesion, lbs./in. | 2.0 | PSTC-2 (30 min. applied) |
| Temperature Ranges | | |
| Minimum Application | +35°F (1.6°C) | CTM #45 Curwood |
| Service Ranges | -65°F to +180°F (-54°C to +82°C) | Polyester Film Dry Surface |

Liner A cost effective white kraft liner with scores every 1 ¼", has outstanding lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.

Typical Physical Properties of Liner

| | | |
|---|---------------|-------------|
| Caliper, inches | 0.0042+/- 10% | TAPPI T-411 |
| Basis Weight, lbs. (24" x 36"/500 sheets) | 72 +/- 10% | TAPPI T-410 |

Total Caliper 0.0086 ± 10% inches (8.6 mils)

Printing Process

Printable by offset-lithography and screen-printing process with ink systems compatible with this product. Laser compatible with production sized toner fusion printers capable of using heavier weight materials. Use laser compatible inks if pre-printing. Follow printer manufacturer's recommendations on printing pressure sensitive media and always test.

Shelf Life

Two years when stored at 72° F and 50% R.H.

This product complies with CONEG regulations.

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

www.Mactac.com

