



**Metro**

Updated 10/13

**Satin Litho**

	Sheet Size	Sheet Size	Sheet Size
<b>Stock Numbers</b>	NY 2021 8-1/2" x 11"	NY 2022 17" x 22"	NY 2023 26" x 20"

**Construction**

- Face:** Satin Finish Litho
- Adhesive:** General purpose permanent acrylic adhesive
- Liner:** Scored release liner. Back printed in red "Metro"

**Description**

<b>Face</b>	An economical satin finished sheet.		
	<b>Typical Physical Properties of Face Stock without Adhesive</b>		
	Caliper, inches	0.0035 +/- 10%	TAPPI T-411
	Tear, grams	53 MD 55 CD	TAPPI T-414
	Tensile, lbs./in.	31 MD 17CD	TAPPI T-494
	Basis Weight, lbs. (25" x 38"/500 sheets)	60 +/- 10%	TAPPI T-410
<b>Adhesive</b>	General Purpose Permanent bonds well to a wide variety of surfaces. It is especially formulated to all but eliminate sheet edge adhesive bleed.		
	<b>Typical Physical Properties of Adhesive</b>		
	Thickness, inches	0.0007 +/- 10%	
	Peel Adhesion, lbs./in.	2.0	PSTC-2 (30 min. applied)
	Temperature Ranges		
	Minimum Application	+35°F (1.6°C)	CTM #45 Curwood
	Service Ranges	-65°F to +180°F (-54°C to +82°C)	Polyester Film Dry Surface
<b>Liner</b>	A cost effective white kraft liner with scores every 1 1/4", has outstanding lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.		
	<b>Typical Physical Properties of Liner</b>		
	Caliper, inches	0.0042 +/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410
<b>Total Caliper</b>	0.0084 ± 10% inches (8.4 mils)		
<b>Printing Process</b>	Printable by offset-lithography and screen-printing process with ink systems compatible with this product.		
<b>Shelf Life</b>	Two years when stored at 72° F and 50% R.H.		
	This product complies with CONEG regulations.		

**IMPORTANT NOTICE:** The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

[www.Mactac.com](http://www.Mactac.com)

