



Starliner Label Products Offset Labels / White Rectangles

04/10
Revised by CEK

Description

60# smooth uncoated litho with permanent adhesive and lay flat liner in a variety of popular label sizes. Matrix removed for faster end use application. Not recommended for laser printing because of matrix removal. Over time, the silicone from the exposed liner may contaminate the laser drum causing sheets to mis-feed and jam.

Applications and End Uses

Labels for economical printing, writing, typing and other graphic uses. Saves time and money by eliminating die cutting.

Stock Number	Label Size	Sheet Size	Number of Labels	Sheets/Box	Stock Number	Label Size	Sheet Size	Number of Labels	Sheets/Box
SR6006	3/8" x 1 1/4"	8 5/16" x 11 1/2"	152	100	SR6017	3" x 2"	6 1/8" x 11 1/2"	10	100
SR6008	1/2" x 1 3/4"	8 7/16" x 11 1/2"	90	100	SR6026	3" x 5"	9 3/16" x 11 1/2"	6	100
SR6007	7/8" x 5/8"	7 1/2" x 11 1/2"	112	100	SR6046	3" x 5"	6 1/4" x 11 1/2"	4	100
SR6040	1 3/8" x 3/4"	6" x 11 1/2"	48	100	SR6042	3 1/4" x 2"	6 3/4" x 11 1/2"	10	100
SR6010	1 1/2" x 1"	7 7/8" x 11 1/2"	50	100	SR6020	4" x 1 1/4"	8 1/2" x 11"	16	100
SR6014	1 3/4" x 1 1/4"	7 1/4" x 11 1/2"	32	100	SR6043	4" x 1 15/16"	8 1/2" x 11"	10	100
SR6009	2" x 1"	8 1/4" x 11 1/2"	40	100	SR6018	4" x 2"	8 1/8" x 11 1/2"	10	100
SR6011	2" x 1 1/2"	8 1/4" x 11 1/2"	24	100	SR6019	4" x 2 1/2"	8 1/8" x 11 1/2"	8	100
SR6012	2 3/4" x 1"	8 7/16" x 11 1/2"	30	100	SR6044	4" x 3"	8 1/4" x 11 1/2"	6	100
SR6015	2 3/4" x 1 1/2"	8 7/16" x 11 1/2"	18	100	SR6077	4" x 5"	8 1/4" x 11 1/4"	4	100
SR6013	3" x 1"	6 1/8" x 11 1/2"	20	100	SR6045	4 1/8" x 3 3/16"	8 1/2" x 11 1/2"	6	100
SR6016	3" x 1 1/2"	6 1/8" x 11 1/2"	14	100	SR6021	4 3/16" x 3 1/4"	8 1/2" x 11 1/2"	6	100

Face

60# smooth bright white uncoated litho designed for offset lithography

Typical Physical Properties of Face Stock without Adhesive

Caliper, inches	0.0047 +/- 10%	TAPPI T-411
Brightness	94	TAPPI T-452
Tear, grams	60 MD 69 CD	TAPPI T-414
Tensile, lbs./in.	35 MD 13.5 CD	TAPPI T-494
Smoothness, Sheffield Units	155	TAPPI T-538
Basis Weight, lbs. (25" x 38"/500 sheets)	60 +/- 10%	TAPPI T-410

Adhesive

A permanent acrylic adhesive with excellent ultimate adhesion to a wide variety of substrates. Patented to virtually eliminate ooze during laser printing.

Typical Physical Properties of Adhesive

Thickness, inches	0.0007 +/- 10%	
Peel Adhesion, lbs./in.	1.7	PSTC-2 (30 min. applied)
Temperature Ranges		
Minimum Application	+35°F (1.7°C)	CTM #45 Curwood
Service Ranges	-75°F to +200°F (-59°C to +93°C)	Polyester Film Dry Surface



Starliner Label Products

Liner A nominal 50# semi bleached white kraft liner has excellent lay-flat characteristics and internal strength, toughness and tear resistance

Typical Physical Properties of Liner

Caliper, inches	0.0032+/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	52 +/- 10%	TAPPI T-410

Total Caliper ($\pm 10\%$)	Inches	Mils (0.001 inch)	Microns
	0.0085"	8.5 mils	216 μ

Printing Process Offset-lithography. Impact printable

Shelf Life One year when stored at 72° F and 50% R.H.

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

