

www.Mactac.com



Updated 09/11

**Prestige TF Clear**  
Matte Clear Vinyl - **Ultra Removable** for Production Digital Presses

Stock Number	TFC2012	Sheet Size 12" x 18"	Sheets /Carton 100	
<b>Construction</b>		<b>Applications and End Uses</b>		
<b>Face:</b>	Clear Matte Vinyl for sheet fed digital printing		Sheet fed production sized dry toner fusion presses. Use for POP, bumper sticker, cooler displays, window displays, and menu boards. Always follow OEM's recommendations for pressure sensitive media and test thoroughly.	
<b>Adhesive:</b>	Ultra Removable			
<b>Liner:</b>	Specially processed release liner.			
<b>Face</b>	Base face stock is a 3.4 mil matte clear calendared vinyl. This durable, flexible, vinyl conforms well to irregular surfaces.			
<b>Typical Physical Properties of Face Stock with Adhesive</b>				
<b>Caliper</b> , inches	0.0034 ± (3.4 mils)		TAPPI T-411	
<b>Gloss</b>	83%		TAPPI T-452	
<b>Adhesive</b>	An ultra removable acrylic adhesive removes cleanly up to 6 months from most flat surfaces such as glass, painted walls, painted metal, hard plastics. Recommend testing for intended use.			
<b>Typical Physical Properties of Adhesive</b>				
Temperature Ranges				
Minimum Application	+45°F (7°C)		CTM #45 Curwood	
Service Ranges	-20°F to +150°F (-29°C to +66°C)		Polyester Film Dry Surface	
<b>Liner</b>	A nominal 80# white kraft liner with scores has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.			
<b>Typical Physical Properties of Liner</b>				
Caliper, inches	0.0042+/- 10%		TAPPI T-411	
Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%		TAPPI T-410	
<b>Total Caliper</b>				
<b>Typical values +/-10%</b>	Inches	Mils (0.001 inch)	Grams Meter Square	Microns
	0.0085"	8.5 mils	245 g/m <sup>2</sup>	215.9μ
<b>Printing Process</b>	Production sized dry toner fusion digital sheet fed presses			
<b>Shelf Life</b>	One year when stored at 70° F and 50% R.H.			

This product complies with CONEG regulations

**For ordering and product information call 1-800-321-8834**

**IMPORTANT NOTICE:** The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

<sup>®</sup> Registered Trademark of Morgan Adhesives Company.

