



## Prestige TF White

White Vinyl - **Ultra Removable** for Production Digital Presses

		Sheet Size	Sheets /Carton	
Stock Number	TFW2012	12" x 18"	100	
	<b>Construction</b>		<b>Applications and End Uses</b>	
Face:	White Vinyl for sheet fed digital printing		Sheet fed production sized dry toner fusion presses. Use for POP, bumper sticker, cooler displays, window displays, and menu boards. Always follow OEM's recommendations for pressure sensitive media and test thoroughly.	
Adhesive:	Ultra Removable			
Liner:	Specially processed scored release liner.			
Face	Base face stock is a 3.5 mil white matte calendared vinyl. This durable, flexible, vinyl conforms well to irregular surfaces.			
	<b>Typical Physical Properties of Face Stock with Adhesive</b>			
	Caliper, inches	0.0035 ± (3.5 mils)		TAPPI T-411
	Brightness	37.5		TAPPI T-480
	Gloss	83%		TAPPI T-452
Adhesive	An ultra removable acrylic adhesive removes cleanly up to 6 months from most flat surfaces such as glass, painted walls, painted metal, hard plastics. Recommend testing for intended use.			
	<b>Typical Physical Properties of Adhesive</b>			
	Temperature Ranges			
	Minimum Application	+45°F (7°C)		CTM #45 Curwood
	Service Ranges	-20°F to +150°F (-29°C to +66°C)		Polyester Film Dry Surface
Liner	A nominal 80# white kraft liner with scores every 1 ¼", has excellent lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.			
	<b>Typical Physical Properties of Liner</b>			
	Caliper, inches	0.0042+/- 10%		TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%		TAPPI T-410
Total Caliper				
Typical values +/-10%	Inches	Mils (0.001 inch)	Grams Meter Square	Microns
	0.0088"	8.8 mils	267 g/m <sup>2</sup>	223.52μ
Printing Process	Production sized dry toner fusion digital sheet fed presses			
Shelf Life	One year when stored at 70° F and 50% R.H.			

This product complies with CONEG regulations

**IMPORTANT NOTICE:** The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

<sup>®</sup> Registered Trademark of Morgan Adhesives Company.

