

2020 | Product

February | Vehicle Media

NEW Generation B•free vehicle wrap media
including a slide-able adhesive system for faster & easier installation!



Available in 150' and new 75' lengths! Ask about our bundle pricing.

What NEW about is B-free® GRUV vehicle media?

GVC929v2BFD - Featuring Slide-able bubble-free adhesive technology, the new B-free Slide-able GRUV (GVC929v2BFD) promises faster, easier graphic installation on vehicles, busses, fleets and more.

The slide-able, bubble-free air-egress acrylic pressure-sensitive adhesive, which features an omni-directional invisible adhesive pattern, is paired with a 2.0 mil gloss white, soft cast PVC film that is known for excellent color reproduction and a 90# poly-coated layflat liner for superior stability during the printing process. The unprinted film has an unprinted outdoor durability of 10 years.

GV729v2BFD - Thinner, more conformable. Designed for partial wraps, flat and simple curves and long term signage, GV729v2BFD combines excellent performance and economics. Perfect for partial and full wraps and longer term signage.

ICC profiles can be downloaded at mactac.com

Product	Gauge	Adhesive	Liner	Unprinted Outdoor Durability
GVC929v2BFD	2.0 mil gloss white, soft cast PVC	Slide-able Bubble-free, Air-egress	90# Polycoated	10 years
GV729v2BFD	2.1 mil soft white gloss, highly conformable, laminated PVC	Bubble-free, Air-egress	80# Polycoated 2-side Release Liner	7 years

Durability

- Use-life estimate based on accelerated age studies on vertical applications under “normal” environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to Mactac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit mactac.com to download.

Temperature Ranges

- Minimum Application: +50°F (+10°C)
- Gruv 729 End Use: -5° to 195°F (-20° to 70°C)
- Gruv 929 End Use: -5° to 250°F (-20° to 121°C)

Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.

For more information about B-free Gruv v2 or other Mactac products, partnerships or graphic solutions, call a graphics representative at **866-622-8223**, e-mail Mactac.Americas@mactac.com or visit mactac.com/graphics.

