

macbond[®]

XT

Applications

Foam Fabrication | Gaskets | Seals

Insulation & Sound Dampening | Automotive | Mounting

Laminating | Packaging



Gaskets



Insulation
& Sound
Dampening



Automotive



RV/Commercial
Vehicles



General
Mounting



Foam
Fabrication




Laminating



Building &
Construction



Packaging



Features

- Aggressive, high tack rubber-based adhesive
- 0.5 mil PET carrier
- Multiple coat weights available
- Excellent shear properties
- SCK, PCK, PET and 12 pt tag liners available

Benefits

- XT Rubber provides superior adhesion to most foams, felts, cloths, primed wood, paper, metal, plastics and most low or unplasticized substrates.
- Good LSE performance
- Dimensionally stable carrier for superior die cutting
- Cost effective

We're Solid.
100% 

mactac[®]
Industrial Tapes and Adhesives

Mactac[®] is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.

macbond[®]

XT

Products Featuring MP593XT Rubber Adhesive

Application Temperature +50°F

Service Temperature 0°F - 180°F

Double Coated Tapes

Part Number	Carrier	Coat Weight		Liner	Master Roll		Performance Characteristics		
		Liner	Unwind		Width	Length	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
IB1111XT	.5mil PET	2.0	2.0	60# White SCK	54"	750'	12.0	12.0	500+
IB1175XT/W60	.5mil PET	2.0	2.0	80# White SCK	54" or 60"	750'	12.0	12.0	500+
IB1175XTL12	.5mil PET	2.0	2.0	12pt Board	54"	750'	12.0	12.0	500+
IB1178XT	.5mil PET	1.2	1.2	60# White SCK	54"	750'	10.0	10.0	500+
IB1178XTPK	.5mil PET	1.2	1.2	72# White PCK	54"	750'	12.0	12.0	500+
IB1182XT	.5mil PET	1.2	1.2	60# White SCK	54"	750'	10.0	10.0	500+
IB1183XT/W60	.5mil PET	2.0	2.0	80# White SCK	54" or 60"	750'	12.0	12.0	500+
IB1184XTW60	.5mil PET	2.6	2.6	80# White SCK	60"	750'	14.0	14.0	500+
IB1185XTL12	.5mil PET	2.0	2.0	12pt Board	54"	750'	12.0	12.0	500+
IB1188XT	.5mil PET	2.0	2.0	80# White SCK	54"	750'	12.0	12.0	500+
IB1190XT/W60	.5mil PET	2.0	2.0	60# White SCK	54" or 60"	750'	12.0	12.0	500+
IB1200XTW60	.5mil PET	2.6	2.6	80# White SCK	60"	750'	14.0	14.0	500+

Transfer Adhesive - Double Coated Tapes

Part Number	Adhesive	Coat Weight	Caliper mils	Liner	Master Roll		Performance Characteristics		
					Width	Length	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
IF1011-78	XT Rubber	1.8	6.5	78# SCK	60"	540'	12.0	12.0	500+
IF1013-78	XT Rubber	2.6	8.3	78# SCK	60"	540'	12.0	12.0	500+

MP593XT complies with all REACH and RoHS regulations

Automotive Specifications

Mactac's 593XT products are verified by an accredited third-party testing laboratory to meet the adhesive requirements for the specifications listed below.

Manufacturer	Specification	Mactac Product
GM	16443, 14729	IB1190XT, IB1183XT, IB1175XT
Ford	ESB-M3G76-B2	IB1190XT, IB1183XT, IB1175XT

For additional Performance Guides on MP593 XT, please visit www.mactac.com.

Mactac is ISO9000-2000 certified.

Mactac is a member of the following organizations:

Gasket Fabricators Association

National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)

Pressure Sensitive Tape Council (PSTC)

