



PERFORMANCE GUIDE

Represents Typical Values Only

www.Mactac.com

FSC® SG2602
INDIE® Semi Gloss

Revised: 02/2014 AKB



Description

Product ISG2602 is a 60# Indigo printable semi gloss facestock with an all temperature acrylic adhesive and a 2.45 mil semi-bleached calendared kraft liner. FSC Certified. Certificate Number: FSC-C161021

Applications and End Uses

For prime labeling applications requiring a semi gloss paper. Markets include: Food, cosmetic, toiletries and more.

HP Indigo Certification 3 Stars
RI4050-12-2535 & RI6000-12-2535

Face

60# Indigo printable semi gloss facestock designed for quality printing and high speed converting.

Physical Properties Without Adhesive

Caliper, inches	0.00335 +/- 10%	TAPPI T-411
Brightness % Reflectance at 75° angle	81	TAPPI T-452
Gloss % Reflectance at 75° angle	71	TAPPI T-480
Opacity	90	TAPPI T-425
Tear, grams	42 MD 50 CD	TAPPI T-414
Tensile, lbs./in.	36 MD 16 CD	TAPPI T-494
Basis Weight, lbs. (25" x 38"/500 sheets)	63 +/- 10%	TAPPI T-410

Adhesive

An all temperature acrylic adhesive that performs in both cold and damp environments and in elevated temperature applications. 640 AT converts well on today's faster and wider presses. 640AT exhibits some open time on some substrates (please test) and develops a permanent bond to a wide variety of substrates.

Physical Properties of Adhesive

Thickness, inches	0.0007 +/- 10%	
Peel Adhesion, lbs./in.	1.8 or paper tear	PSTC-101F (30 min. applied)
Temperature Ranges		
Minimum Application	-20°F (-29°C) on most surfaces	
Service Ranges	-40°C to +200° F (-40 to +93°C)	

Liner

A semi-bleached calendared kraft liner excellent for die cutting, stripping and label dispensing. Primarily for roll -to -roll applications.

Caliper, inches	0.00245 +/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	40 +/- 10%	TAPPI T-410

WS6000 Press Parameters

Suggested Press settings recommended by RIT through Certification on WS6000 Testing Performed July 2012. <http://printlabcert.cias.rit.edu/industrialcertifiedmedia>

Best Working Point

Results without White Ink

PTH temperature

0

Feed Fan

8

Blanket temperature

105

2nd Transfer pressure

300

Shelf Life

One year when stored at 72° F and 50% R.H.

This product complies with CONEG regulations.

All Mactac Roll Label products meet the requirements of the Clean Air Act of 1990.

Note: The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances, please contact your Mactac sales representative to discuss your requirements for recommendations. If this is a printed Performance Guide, it is an uncontrolled document. Please check the Mactac website for the latest, most up-to-date version at www.mactac.com

ISG2602 has been independently evaluated and qualified by Rochester Institute of Technology for use on HP Indigo WS4050 & WS6000 digital presses. Reference certificate number from RIT: RI4050-12-2535 & RI6000-12-2535.

CALL 1-800-548-3456 for additional product information



PERFORMANCE GUIDE

Represents Typical Values Only

www.Mactac.com

CALL **1-800-548-3456** for additional product information

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

