

## LTCOT5050 2 Mil Clear Polyester / Oil Tolerant / 60#

Revised: 03/21 CNS

### Description

<b>Product</b>	LTCOT5050 - 2 mil topcoated clear polyester with an oil tolerant acrylic adhesive and a 60# blue glassine liner.	<b>Applications and End Uses</b>
		Designed for use on oily surfaces in applications such as steel, automotive parts, cosmetics, oiled woods, and foods.

### Face

2.0 mil topcoated clear polyester film designed for excellent printing, converting, and dispensing. Print test product and consult with your ink supplier to confirm suitability for your application. 80% PCW within facestock

#### Physical Properties Without Adhesive

Caliper, inches	0.002 (2.0 mils)	ASTM D-2103
-----------------	------------------	-------------

### Adhesive

Oil tolerant is an acrylic adhesive that absorbs oils, enabling strong adhesion to lubricated surfaces. No surface degreasing required and more efficient application.

#### Physical Properties of Adhesive

Thickness, inches	0.001 +/- 10%	
180° Peel Adhesion, lbs./in.	Stainless Steel: 3.7	CTM-8 (30 min. applied) Reference: PSTC-101A
Minimum Application Service Ranges	+41°F (+5°C) -40°F to 212°F (-40°C to +100°C)	CTM #45 Curwood Polyester Film Dry Surface

### Liner

A 60# blue glassine liner. Excellent for die-cutting and stripping. The liner is coated with a release system designed for label dispensing. Primarily for roll-to-roll applications where a more demanding liner is needed.

Caliper, inches	0.0035 +/- 10%	TAPPI T-411
Basis Weight, lbs. (24" x 36"/500 sheets)	60 +/- 10%	TAPPI T-410

**Shelf Life** One year when stored at 72° F and 50% R.H.

This product complies with CONEG regulations.

All MACTac Roll Label products meet the requirements of the Clean Air Act of 1990.

**\* NOTE:** Thermal transfer printing quality and bar code scannability are dependent upon the interworking of several elements; the ribbon, the printhead, and the facestock. Please test all applications. Consult MACTac's Technical Marketing Department for guidelines regarding printer and ribbon compatibility.

**IMPORTANT NOTICE:** The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

<sup>\*</sup> Registered Trademark of Morgan Adhesives Company.

Tide<sup>®</sup> Registered Trademark of the Procter & Gamble Company

409<sup>®</sup> Registered Trademark of the Clorox Company

