

## **PERFORMANCE GUIDE**

Updated **Metro Digital** 11/19



## White Vinyl Ultra Removable for Indigo and Toner Fusion Presses

	Sneet	Sneets /	Liner Description
MDV1218WUS-5	12" x 18"	500	Scores every 1 1/4"
MDV1319WUS-5	13" x 19"	500	Scores every 1 ¼"
		MDV1218WUS-5 12" x 18" MDV1319WUS-5 13" x 19"	MDV1218WUS-5 12" x 18" 500

Construction

**Face:** White vinyl for commercial HP Indigo and toner fusion presses

**Adhesive:** Ultra removable acrylic adhesive

**Liner:** Lay flat liner

Description

Matte white vinyl optimized for sheet fed HP Indigo presses **Face Typical Physical Properties of Face Stock without Adhesive** 

Caliper, inches 0.0034 +/- 10% **TAPPI T-411** 

**Adhesive** An ultra-removable acrylic adhesive removes cleanly up to 6 months from most flat

surfaces such as glass, painted walls, painted metal, hard plastics. Recommend testing for

**Typical Physical Properties of Adhesive** 

**Temperature Ranges** 

CTM #45 Curwood Minimum Application +45°F (7°C) Polyester Film Dry

**Service Ranges** -20°F to +150°F (-29°C to +66°C) Surface

Liner A cost effective white kraft liner has outstanding lay-flat characteristics and internal

strength, toughness, tear resistance for kiss cutting.

**Typical Physical Properties of Liner** 

Caliper, inches 0.0046+/- 10% **TAPPI T-411** Basis Weight, lbs. (24" x 36"/500 sheets) 72 +/- 10% **TAPPI T-410** 

**Total Caliper** 0.0088 ± 10% inches (8.8 mils)

**GSM** 267 ± 10%

**Printing Process** Sheet fed commercial toner fusion and HP Indigo presses

**Shelf Life** One year when stored at 72° F and 50% R.H.

This product complies with CONEG regulations.

IMPORTANT NOTICE: The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC
www.Mactac.com

