

593XT Rubber Transfer Adhesives



Cost effective, versatile performance.

Mactac is a market leader in hot-melt rubber adhesive formulation and coating technology. We are proud to offer our proprietary rubber-based pressure sensitive adhesive in a transfer adhesive form. This high performance tape will provide high-tack, high-shear characteristics with ultimate conformability and ease of use for laminating and assembly projects.

Applications:



Gaskets



General Mounting



Laminating



Insulation Bonding



Foam Fabrication



Packaging



Building & Construction

Features

- Aggressive rubber-based adhesive
- Excellent shear properties
- Bleached white 78# SCK liner

Benefits

- XT Rubber provides superior adhesion to most foams, felts, cloths, primed wood, paper, metal, plastics and most low or unplasticized substrates.
- Good LSE performance
- Dimensionally stable liner for superior die cutting
- Cost effective

Mactac®

593XT Rubber Transfer Adhesives

Products Featuring MP593XT Rubber Adhesive

Application Temperature +50°F

Service Temperature 0°F - 180°F

Double Coated Tapes										
			Caliper mils		Master Roll			Performance Characteristics		
Part Number	Adhesive	Coat Weight	Adhesive & Liner	Liner	Release	Width	Length	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
IF1011-78	XT Rubber	1.8	6.5	78# SCK	Medium	60"	540'	12.0	12.0	500+
IF1013-78	XT Rubber	2.6	8.3	78# SCK	Medium	60"	540'	12.0	12.0	500+

MP593XT complies with all REACH and RoHS regulations

For additional Performance Guides on 593 XT, please visit www.mactac.com/industrialtapes.

Mactac is ISO9000-2000 certified.

Mactac is a member of the following organizations:

Gasket Fabricators Association

National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)

Pressure Sensitive Tape Council (PSTC)

