

Windows

Product Guide



Frosted, dusted, and clear bubble-free digital media for easier application of window graphics.



Windows

Product Guide

The market's first dry application large scale window graphics. The only tools you'll need for a perfect application are tape and a squeegee.







What are B•free® Window Films?

JX5796MBFv2 Frosted and **JX5798MBFv2 Dusted** are 3.1 mil matte translucent vinyl with special finishes for etched, sandblasted, or frosted effects. **JX5999MBFv2 Clear** is a 3.1 mil gloss clear vinyl. Graphics can be printed in reverse to be read through glass. The clear acrylic permanent adhesive features proprietary Mactac bubble-free structure for fast, easy, no-mess DRY application and a smooth print surface. **Cuts your application time in half!**

Where does B-free Frosted, Dusted and Clear Perform?

B•free Window films can be printed by **solvent, eco-solvent, latex** and **UV** wide-format machines and are designed to be used on flat or simply curved clear and translucent surfaces and for backlit graphics.

- Bubble-free technology - eliminates trapped air in every direction
- Smooth print surface for high quality printing
- Ideal for reverse printed graphics where outdoor signage may be restricted
- Can be used for privacy screens

| Product Code | Face | Adhesive | Liner | Width | Durability | Window Media | | | | Recommended Overlaminates |
|------------------------|--|---------------------------------|---------|-------|--|-----------------|------------|----------|----------|---------------------------|
| | | | | | | Dry Application | Lightboxes | Interior | Exterior | Colorgard® LUV |
| Frosted JX5796MBFv2 |  Matte, Frosted Translucent Vinyl | Air Egress Permanent Acrylic | 90# LFP | 54" |  | ■ | ■ | ■ | ■ | ■ |
| Dusted JX5798MBFv2 |  Matte, Dusted Translucent Vinyl | Air Egress Permanent Acrylic | 90# LFP | 54" |  | ■ | ■ | ■ | ■ | ■ |
| Clear JX5999MBFv2 |  Gloss, Clear Vinyl | Air Egress Permanent Acrylic | 90# LFP | 54" |  | ■ | ■ | ■ | ■ | ■ |

Durability

- Use-life estimate based on accelerated age studies on vertical applications under "normal" environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to Mactac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit mactac.com to download.

Temperature Ranges

- Minimum Application: +50°F (+10°C)
- End Use: -40° to 194°F (-40° to 90°C)

Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.

* For plotter cut décor applications, **Macmark® 700 series Décor film** is recommended for an ideal finish.

LFP - Layflat polycoated

For more information about B•free or other Mactac products, partnerships or graphic solutions, call a graphics e-mail Mactac.Americas@mactac.com or visit mactac.com/graphics.