

### MATTE CLEAR POLYMERIC OVL MR10182

#### PRODUCT DESCRIPTION

3.0 mil matte clear polymeric film designed as an overlamine to protect and prolong the life of PVC calendared films and print medias.

#### APPLICATIONS

- Vehicle graphics, partials flat and simple curves
- Transit and fleet, flat and simple cures
- Medium term outdoor signage and advertising
- P.O.P displays

#### FEATURES AND BENEFITS

- Medium term outdoor stable
- Stabilizes and prolongs the life of PVC calendared films and print medias
- Printing Methods: Generally, not used for printing. This film is an overlamine for films and print media. Testing for suitability between media, prints and inks is always recommended before use.

#### TECHNICAL DATA

Face Material	3.0 mil Polymeric
Color and Finish	Matte Clear
Adhesive	Permanent solvent 07 with UV stabilizers
Liner	78# Clay coated Kraft

#### TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 32 oz.	<u>24 hr.</u> 51 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-50°F to +225°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability (ASTM G53)	5 year	

#### SUBSTRATE PREPERATION

All surfaces should be thoroughly cleaned and dried prior to applying the film. Handle the film with care to prevent damage, fingerprints, dirt or other types of imperfections that will show on the finished product. A small test is recommended to insure compatibility between all involved components.

#### APPLICATION

A roll or table laminator is always recommended for a wrinkle and bubble free application of this product to a film or print media.

**IMPORTANT NOTICE:** The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

