

ECONOMY FLOOR ACTION

PRODUCT CODE: MR39829


PRODUCT DESCRIPTION

Ideal for temporary and short-term durability (6 months). This overlamine product is an excellent choice for economical floor graphics applications when used with Mactac's floor graphic media. This product is offered on a film liner for excellent wet out and is UL-410 classified for slip resistance.

APPLICATIONS

- Floor graphics
- Point of purchase displays
- Counter graphics

FEATURES AND BENEFITS

- Environmentally friendly 
- Clear textured
- UL-410 classified for slip resistance

TECHNICAL DATA

Face Material	3.75-mil polyolefin
Color and Finish	Clear textured
Adhesive	22, overlaminating permanent solvent
Liner	1.2 mil clear film

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 65 oz.	<u>24 hr.</u> 75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Indoor Durability	6 months* under normal conditions	
Outdoor Durability	Indoor use only	

*Edge sealer can be applied to protect the edges of your graphics from potential lifting and curling that occurs from contamination or cleaning. The sealer should be tested to determine suitability with overlamine.

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hr)	No Effect

Due to the tensile and elongation properties of the film, impact die cutting such as rotary die and steel rule may cause challenges. Ritrama recommends testing in advance.

*Does not constitute a guarantee of performance but indicates the expected performance based on ordinary wear and tear. The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

CALL 1-800-321-8834 for additional product information

IMPORTANT NOTICE: The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

[®] Registered Trademark of Morgan Adhesives Company.

