

# Macbond® Differential Tapes

## Engineered Tapes & Laminates

Bag Closure Tape

Credit Card  
Mailers

Shelf Marking

POP &  
Promotional  
Displays

Gaskets




Mactac® is a leading supplier of double sided tapes for industry. Our line of differential double sided tapes offers a range of performance options.



# Macbond® Differential Tapes

## Engineered Tapes & Laminates

Minimum App Temperature      +50°  
Service Range:                      -40°F to 180°F (-40°C to 82°C)



### Double-Coated Tapes

Construction							Master Roll		Performance Characteristics		
Part Number	Carrier	Adhesive	Coat Weight Mils		Liner	End Use	Width	Length	Peel SS (U) lbs/in	Tack SS (L) lb/sq.in	Shear hours
			Liner	Unwind		Release					
IB5121-72	.5 mil PET	XT / Low Tack Acrylic	1.0	1.2	72# White PCK	Medium	60"	750'	9.0	0.5	500+
IB5131-72	.5 mil PET	XT /Agressive Removable	1.0	1.2		Medium	60"	750'	9.0	2.0	500+
IB5161-72	.5 mil PET	Permanent 899 / Low Tack Acrylic	1.0	2.0		Medium	60"	750'	8.5	0.5	500+

For Regulatory Information, please visit [www.mactac.com](http://www.mactac.com) for all product regulatory compliance.  
For Quality information, please visit [www.mactac.com/quality](http://www.mactac.com/quality) for all manufacturing site ISO 9001 certificates.

For Technical Data Sheets please visit [www.mactac.com/industrialtapes](http://www.mactac.com/industrialtapes).

Mactac is a member of the following organizations:  
Gasket Fabricators Association  
Pressure Sensitive Tape Council

© 2024 Morgan Adhesives Company, LLC  
MAC4182 (01/24)  
Mactac and Macbond are trademarks of Morgan Adhesives Company, LLC

**mactac**   
A LINTEC COMPANY

Customer Service 800-548-3456

Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898  
email [mactac.americas@mactac.com](mailto:mactac.americas@mactac.com) | [www.mactac.com/industrialtapes](http://www.mactac.com/industrialtapes)