

macbond®

HI/LO

Applications

Bag/Envelope Closures | Window Mounting

Promotional | Shelf Marking

Assembly Aid | Carpet Tape



Bag Closure
Tape



Credit Card
Mailers



Shelf Marking



POP &
Promotional
Displays



Gaskets



Features

- Strong .5 mil PET Carrier
- Aggressive Rubber Adhesive (Unwind)
- Clean Removing Acrylic (Liner)

Benefits

- Excellent handling characteristics and easy to die cut
- High initial tack and adhesion to foams, low surface energy materials and most fabrics.
- Clean removability from many surfaces including glass, plastic, metal and paper.
- Aggressive rubber bonds to all types of carpet and floor mats, acrylic adhesive removes cleanly from most flooring.

We're Solid.
100% 

mactac®
Industrial Tapes and Adhesives

Mactac® is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.

macbond®

HI/LO

Application Temperature +50°F
 Service Temperature 0°F - 180°F

Double Coated Tapes

Part Number	Carrier	Construction			Master Roll Dimensions		Performance Characteristics		
		Coat Weight - mils		Liner	Width	Length	Peel SS (U) lbs/in	Tack SS (L) lb/sq.in	Shear hours
		Unwind	Liner						
IB5121-72	.5 mil PET	1.2	1.0	72# PCK	54"	750'	9.0	0.5	500+
IB5131-72	.5 mil PET	1.2	1.0	72# PCK	54"	750'	9.0	2.0	500+
IB5161-72	.5 mil PET	2.0	1.0	72# PCK	54"	750'	8.5	0.5	500+

Macbond HI/LO complies with all REACH and RoHS regulations

For additional Performance Guides on Macbond HI/LO,
 please visit www.mactac.com.

Mactac is ISO9000-2000 certified.
 Mactac is a member of the following organizations:
 Gasket Fabricators Association
 National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)
 Pressure Sensitive Tape Council (PSTC)



Customer Service 800-548-3456 | Inside Sales 800-328-2619
 Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898
 email Mactac.Americas@Mactac.com • Mactac.com/industrialtapes