Macbond Arctic®

Engineered Tapes & Laminates



Macbond Arctic's unique adhesive formulation offers aggressive peel and tack at temperatures as low as -10F. Let Arctic extend your building season or most challenging cold temperature application today!






Macbond Arctic[®]


Engineered Tapes & Laminates

Minimum App Temperature Service Range: -10° (-23°C) -65°F to 150°F (-54°C to 65.5°C)



Double-Coated Tapes

Construction								Master Roll		MSI	0	il SS	HDPE	Shear
Part Number	Carrier	Adhesive		Coat Weight Caliper Mils Mils			End Use	Width	Length	Weight / I	Stock/MTO	Pee	Peel	Sh
			Liner	Un- wind	Carrier & Adhesive	Liner	Release	Wie	Len	Len We	St	Lbs/ in	Lbs/ in	Hours
ARTX1161	.5mil PET	Arctic MX10	1.5	1.5	3.5	72# White PCK	Medium	60"	750'	0.33	S	7.6	7.3	75+
ARTX1162	.5mil PET		2.0	2.0	4.5		Medium	60"	750'	0.35	S	7.6	7.3	75+



Transfer Adhesives

Construction								Master Roll		0	il SS	HDPE	Shear
Part Number	Carrier	Adhesive	Coat Weight Mils	Caliper Mils		End Use	Width	Length	Weight / MSI	Stock/MTO	Peel	Peel	Sh
				Liner & Adhesive	Liner	Release	Wi				Lbs/ in	Lbs/ in	Hours
ARTX1062	NA	Arctic MX10	2.0	6.4	80# White SCK	Medium	60"	540'	0.33	М	6.2	6	75+

For Regulatory Information, please visit www.mactac.com for all product regulatory compliance. For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates For Technical Data Sheets please visit www.mactac.com/industrialtapes.

Mactac is a member of the following organizations: Gasket Fabricators Association Pressure Sensitive Tape Council

© 2025 Morgan Adhesives Company, LLC MAC4197 (3/25) Mactac, Macbond and Macbond Arctic are trademarks of Morgan Adhesives Company, LLC



Customer Service 800-548-3456 Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898 email mactac.americas@mactac.com | www.mactac.com/industrialtapes