

macbond[®] cold temperature tapes **arctic**

Applications

Packaging & Food Packaging | Freezer/Refrigeration

Insulation & Sound Damping

High tack in Cold, Wet Conditions

General Purpose Bonding Applications | Laminating



Direct Food Contact



Packaging



Bag Closure Tape



Building & Construction



Insulation



Lamination



Features

- Aggressive rubber-based adhesive
- Good cohesive strength
- Dimensionally stable liners

Benefits

- Minimum Application Temperature of -10°F/ -23°C
- Approved for direct food contact complies - with FDA 175.125
- Low Surface Energy Adhesion
- Bonds well to all paper & corrugate materials, including wax coated corrugate.
- Exceptional performance on foams including: XLPE, EPDM, EVA and Polyurethane Materials.

We're Solid.
100% 

mactac[®]
Industrial Tapes and Adhesives

Mactac[®] is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.

macbond[®] arctic

Products Featuring Macbond Arctic Adhesive

Minimum App Temperature -10° (-23°C)
Service Range: -65°F to 150°F (-54°C to 65.5°C)

Part Number	Carrier	Adhesive mils	Liner	Master Roll		Peel SS	Peel HDPE	Shear
				Width	Length	Lbs/in	Lbs/in	Hours
ARTX1162	.5 mil PET	2.0/2.0	72# PCK	60	750'	7.6	7.3	75+
ARTX1062		2.0	83# SCK	60	540'	6.2	6	75+

Macbond Arctic Products comply with the following:

FDA 21 CFR 175.125
REACH and RoHS regulations
Prop 65 compliant
Conflict Minerals
Toxics in Packaging
Consumer Product Safety Act 2008

For additional Performance Guides on MacBond products, please visit www.mactac.com.

Mactac is ISO9001-2015 certified.
Mactac is a member of the following organizations:

Gasket Fabricators Association
Pressure Sensitive Tape Council (PSTC)

