

Macbond® Ultra 555 Series

Engineered Tapes & Laminates



Acoustic Panel
Mounting

Architectural
Detailing

Fixture & Dispenser
Mounting

Interior Signage
& Display

Mirror Mounting

Shiplap & Decorative
Paneling

Sound Damping



Mactac's unique MP555 formula brings the typical benefits of a rubber PSA such as high-tack and peel properties with exceptional cohesive strength. Ultra 555 exhibits superior holding power and offers excellent performance on low surface energy materials.



Macbond® Ultra 555 Series


Engineered Tapes & Laminates

Features


- Ultra-strength pressure sensitive adhesive
- Foam and Film Carriers for ease of handling
- Easy release liner, excellent for all types of installation processes

Benefits

- Ultimate holding power for mounting fixtures, signs or panels with a large profile
- Superior bond to Low VOC paints and low surface energy materials
- Water resistant
- Foam carriers provide excellent cushion between dissimilar surfaces
- Replaces mechanical fasteners



Double Coated Film



Double Coated Foam

Construction								Master Roll		Weight / MSI	Stock/MTO
Part Number	Carrier	Adhesive	Coat Weight Mils		Caliper Mils	Liner	End Use	Width	Length		
			Liner	Unwind	Carrier & Adhesive		Release				
Double Coated Film											
IB8161-78	0.5 mil PET	Ultra 555	1.8	1.8	4.1	78# SCK	Medium	60"	750'	0.39	S
Double Coated Foam											
IM1763-78	1/32 White PE Foam	Ultra 555	2.6	2.6	35.25	78# SCK	Medium	60"	216'	0.39	S
IM1863-78	1/16 White PE Foam	Ultra555	2.6	2.6	66.50	78# SCK	Medium	60"	108'	0.39	S

For additional Performance Guides on Macbond Ultra 555 products, please visit www.mactac.com.

Mactac is ISO9000-2015 certified.

Mactac is a member of the following organizations:

Gasket Fabricators Association

National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)

Pressure Sensitive Tape Council (PSTC)



Customer Service 800-548-3456