

Cleantape™ for E-Mobility

Engineered Tapes & Laminates



Automotive

Bonding

Busbars

Cell Wrapping

Compression Pads

Cushioning & Dampening

Electrical Insulation


EMI & RF Shielding

Pack Sealing & Gasketing

PCK & Flexible Circuit

Thermal Runaway
Protections


Thermal Interface



Cleanest adhesive tape offering available with versatile solutions to help optimize battery safety, performance, power density and streamline manufacturing. Our Cleantapes are uniquely suited for batteries and EVs applications. No VOCs, ultra-low outgassing & migratory properties allow for excellent compatibility, stability and long-term and performance inside the pack.


Cleantape™ for E-Mobility

Engineered Tapes & Laminates



Double Coated Tapes

Part Number	Adhesive	Type	Carrier	Coat Weight (mils)		Caliper (mils)	Liners	Performance Characteristics		
				Liner/Unwind	Adhesive & Carrier			Peel SS lb/in	Tack SS lb/sq.in	Shear hours
CB1100	LV750	Rubber	.5 mil PET	1.2/1.2	2.9		60# SCK/ 72# PCK	12.0	12.0	1000+
CB1102	LV750	Rubber	.5 mil PET	2.0/2.0	4.5		60# & 80# SCK, 12pt Brd	12.0	12.0	1000+
CB4161	LV860	LSE Acrylic	.5 mil PET	1.8/1.8	4.1		72# PCK	8.8	9.0	55+
CB4180	LV820	Acrylic	.5 mil PET	1.2/1.2	2.9		72# PCK/ 80# NT PCK	8.5	6.5	85+
CB4181	LV820	Acrylic	.5 mil PET	1.8/1.8	4.1		72# PCK/ 80# NT PCK	8.5	7.0	85+
CB4182	LV820	Acrylic	.5 mil PET	2.4/2.4	5.3		72# PCK/ 80# NT PCK	9.5	7.0	85+
CB4190	LV840	Acrylic	.5 mil PET	1.2/1.2	2.9		72# PCK	5.5	5.0	300+
CB4190-2PET	LV840	Acrylic	.5 mil PET	1.2/1.2	2.9		2.0 PET liner x2	5.5	5.0	300+
CB4192	LV840	Acrylic	.5 mil PET	2.4/2.4	5.3		72# PCK	6.5	8.0	300+




Transfer Tapes

Part Number	Adhesive	Type	Carrier	Coat Weight		Caliper (mils)	Liners	Performance Characteristics		
				mils	Adhesive & Liner			Peel SS lb/in	Tack SS lb/sq.in	Shear hours
CF1091	LV750	Rubber	NA	1.8	6.5		78# SCK	12.0	12.0	1000+
CF1093	LV750	Rubber	NA	2.6	8.3		78# SCK	12.0	12.0	1000+
CF4062	LV860	LSE Acrylic	NA	2.0	9.8		72# PCK	9.0	9.2	55+
CF4082	LV820	Acrylic	NA	2.0	7.8, 8.1		72# PCK/ 80# NT PCK	9.5	5.5	85+
CF4083	LV820	Acrylic	NA	3.0	8.8, 9.1		72# PCK/ 80# NT PCK	9.5	7.0	85+
CF4084	LV820	Acrylic	NA	4.0	9.8, 10.1		72# PCK/ 80# NT PCK	9.9	7.0	85+
CF4092	LV840	Acrylic	NA	2.0	7.8		72# PCK	6.0	6.0	300+
CF4094	LV840	Acrylic	NA	4.0	8.8		72# PCK	6.5	7.2	300+

- Double liner options are available on acrylic products
- Custom constructions are available upon request
- For the most current information, visit Mactac.com



- Excellent compatibility with various conductive inks, solders and circuitry components.



- High dielectric properties, and insulation properties



- Adhesion to a wide variety of materials including various types of films, foils, foams and thermal interface materials



- Capable of withstanding rigorous hot & cold temperature cycling.



- Low Fog - VDA278 Compliant, SAE J1756



- Withstands exposure to chemicals, organics solvents, cleaners, fuel types, hydrocarbon-based fluids, weak acids and alkalis



- Non-VOC - Meets JIS-A 1901
- Low Outgassing - meets E595 specifications



- Recognized for UL969 and CSA 22.2 No. 15



- **Application Temperature** Above 50°F (10°C) for best performance
- **End Use Temperature** -40°F to 450°F (-40°C to 232°C)*based on adhesive



Cleantape™ for E-Mobility

Engineered Tapes & Laminates

PCB & Flexible Circuit Bonding



Pack Sealing & Gasketing



EMI & Electrical Insulation



Busbars




Cell Wrapping




Compression Pads



Cushioning & Dampening



Thermal Interface



Thermal Runaway Protection



For Regulatory Information, please visit www.mactac.com for all product regulatory compliance.
For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates.
For Technical Data Sheets please visit www.mactac.com/industrialtapes.

Mactac is a member of the following organizations:
Gasket Fabricators Association
Pressure Sensitive Tape Council

© 2023 Morgan Adhesives Company, LLC
MAC4216 ver.2 (10/23)
Mactac and Cleantape are trademarks of Morgan Adhesives Company, LLC

mactac®
A LINTEC COMPANY

Customer Service 800-548-3456 | Inside Sales 800-328-2619
Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898
email mactac.america@mactac.com | www.mactac.com/industrialtapes