Engineered Tapes & Laminates

Mactac Medical Film Tapes & Transfer Films



Our product offering includes single coated films, double coated films and transfer adhesives.. These products have been designed for direct skin contact, provide excellent adhesion and are cleanly removable without causing irritation. All products have been independently tested following ISO-10993 Guidelines.

Applications:

Drape Assembly • Drape to Patient Attachment • Drape Assembly and Securement Device Assembly • IV Securement

Features & Benefits:

EtO and Gamma Sterilizable • Removes Cleanly from Skin • Compatible with Most Drape Materials Bio-Compatiblity Tested • Latex-free




Engineered Tapes & Laminates


Mactac Medical Film Tapes & Transfer Films




Single Coated Film



Double Coated Film



Transfer Adhesives



Product	Carrier	Adhesive	Coat Weight Mils	Liner(s)	Conformable	Fluid Barrier	enic				ster oll	MSI	0
							Hypoallergenic	Latex-free	Custom	Width	Length	Weight / MSI	Stock/MTO
Film Tape - Single Coated													
TM7100 Custom	2.5 mil White Gloss PE	899 HM Rubber	1.0	40# SCK	1	1	1	1	1	60"	750′	0.28	М
TM7101 Custom	2.5 mil Taffeta Embossed PE	899 HM Rubber	1.0	40# SCK	1	1	1	1	1	60"	750′	0.28	М
TM7102 Custom	3.0 mil Tan Matte Polyethylene	899 HM Rubber	1.0	40# SCK	1	1	1	1	1	60"	750′	0.28	М
Film Tape - Doubl	e Coated												
TM8500	.50 mil PET	160 Acrylic	1.2/1.2	2.0 mil PET /2.0 mil PET		1	1	1		60"	750′	0.30	S
TM8510	.50 mil PET	150 Acrylic	1.8/1.8	72# PCK		1	1	1		60"	750′	0.33	S
TM8520	.50 mil PET	150 Acrylic	2.4/2.4	72# PCK		1	1	1		60"	750′	0.35	S
TM8610	.50 mil PET	160 Acrylic	1.2/1.2	72# PCK		1	✓	✓		60"	750′	0.28	S
TM8650	.50 mil PET	160 Acrylic	2.4/2.4	72# PCK		1	1	1		60"	750′	0.35	S
TM8710A	.50 mil PET	899 HM Rubber	2.0/2.0	60# SCK		1	✓	✓		60"	750′	0.35	S
TM8720	.50 mil PET	593 HM Rubber	2.0/2.0	60# SCK		1	1	1		60"	750′	0.35	S
TM8750	.50 mil PET	593 HM Rubber	2.6/2.6	80# SCK		✓	✓	✓		60″	750′	0.38	S
Transfer Adhesive	s												
TM1050	N/A	150 Acrylic	2.0	72# PCK	1		1	1		60"	540"	0.30	S
TM1054	N/A	150 Acrylic	4.0	72# PCK	1		1	1		60"	540"	0.32	S
TM1060	N/A	160 Acrylic	2.0	72# PCK	1		1	1		60"	540"	0.30	S
TM1064	N/A	160 Acrylic	4.0	72# PCK	1		1	1		60"	540"	0.32	S

Please request Mactac Performance Guides for detailed product information. Contact your sales representative or customer service for more information.

Shelf Life: Two years from date of manufacture, when stored at 75°F (24°C) and 50% relative humidity or less. It is recommended the product be stored in its original package, until ready for use.

