

### PRODUCT CODE: 4-2097

#### PRODUCT DESCRIPTION

Gloss clear topcoated polypropylene with a removable adhesive and polyester release liner.

#### APPLICATIONS

- Seal/reseal labels for wet packed products such as:  
baby wipes  
cosmetics  
household products

#### FEATURES AND BENEFITS

- Printable with common printing technologies such as UV letterpress, UV flexography, gravure, and hot stamping
- Adhesive exhibits high shear and moisture resistance
- When used as a resealable label affixed to package that includes a layer of 1 mil or greater of poly(ethylene terephthalate) PET film between the label and food, the product complies for use in contact with all food types under FDA's Condition of Use E ("Room temperature filled and stored (no thermal treatment in the container)") and less severe temperature conditions as set forth in 21 C.F.R. § 176.170(c), Tables 1 and 2, respectively.

#### TECHNICAL DATA

|                  |                                 |
|------------------|---------------------------------|
| Face Material    | 2.0-mil topcoated polypropylene |
| Color and Finish | Clear Gloss                     |
| Adhesive         | Removable acrylic, RS82B        |
| Liner            | 1.2-mil polyester               |

#### TYPICAL CHARACTERISTICS

|  |                                   |                                   |
|--|-----------------------------------|-----------------------------------|
| Target Adhesion Values<br>(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel) | <u>15-min dwell</u><br>0.90 lb/in | <u>24 hr dwell</u><br>1.0 lb/inch |
| Minimum Application Temperature  | 50°F                              |                                   |
| Service Temperature Range  | -22°F to 212°F                    |                                   |
| Shelf Life (@ 73°F, 50% RH)  | 2 years                           |                                   |
| Outdoor Durability   | not recommended                   |                                   |

**IMPORTANT NOTICE:** The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>TM</sup> Trademark of Morgan Adhesives Company.

© Registered Trademark of Morgan Adhesives Company.

