



www.MACtac.com

PERFORMANCE GUIDE

Represents Typical Values Only

PLD2692-2

Revised: 02/2025 MTT

FSC® Platinum™ Plus Semi-Gloss 640AT 1.2 mil PET

Description		Applications and End Uses	
Product	PLD2692-2 is a 50# brilliant white semi-gloss coated litho construction with a general-purpose, permanent adhesive and a 1.2 PET liner.	For prime labeling applications that may be applied at various temperatures. Markets include food, cosmetic, beverage, household cleaners and more.	
Face	Platinum Plus is a 50# basis weight, white semi-gloss coated sheet that has been engineered specifically for use as a pressure sensitive label stock with the Aqueous Flexographic, UV Flexographic, Rotogravure, and UV Rotary Letterpress printing processes in mind. FSC Certified. Certificate Number: SCS-COC-007635		
	Physical Properties Without Adhesive		
	Caliper, inches	0.0024 +/- 10%	TAPPI T-411
	Brightness % Reflectance at 75° angle	90	TAPPI T-452
	Gloss % Reflectance at 75° angle	75	TAPPI T-480
	Opacity	87	TAPPI T-425
	Tear, grams	40 MD 42 CD	TAPPI T-414
	Tensile, lbs./in.	27 MD 13 CD	TAPPI T-494
	Basis Weight, lbs. (25" x 38"/500 sheets)	47.3+/- 10%	TAPPI T-410
Adhesive	640AT is an all temperature permanent, acrylic adhesive that performs well in normal to freezer temperature applications. 640AT exhibits some open time on some substrates (please test) and develops a permanent bond to a wide variety of substrates.		
	Physical Properties of Adhesive		
	Thickness, inches	0.0007 +/- 10%	
	Peel Adhesion, lbs./in.	Corrugate: 1.8	PSTC-101F (30 min. applied)
	Temperature Ranges		
	Minimum Application	-20°F (-29°C)	
	Service Ranges	-65°F to +200°F (-54°C to 93°C)	
Liner	1.2 mil clear polyester liner ideally suited for maximum strength in very high speed automatic dispensing for roll to roll applications.		
	Caliper, inches	0.0012 +/- 10%	TAPPI T-411
Shelf Life	One year when stored at 72° F and 50% R.H		

The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances, please contact your MACtac sales representative to discuss your requirements for recommendations. If this is a printed Performance Guide, it is an uncontrolled document. Please check the MACtac website for the latest, most-up-to-date version.

CALL 1-800-548-3456 for additional product information or visit www.mactac.com

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

[®] Registered Trademark of Morgan Adhesives Company.

