



## Metro Digital

Updated  
10/14

### Semi-Gloss Litho for Toner Fusion Block Out

Stock Numbers		Sheet Size	Sheets / CTN	Liner Description
MTP1218SOPS-2		12" x 18"	200	Standard scores every 1 ¼"
MTP1319SOPS-2		13" X 19"	200	Standard scores every 1 ¼"

#### Construction

<b>Face:</b>	Semi-Gloss litho for commercial toner fusion digital presses with OPAQUE barrier
<b>Adhesive:</b>	General purpose permanent acrylic adhesive
<b>Liner:</b>	Lay flat liner

#### Description

<b>Face</b>	A semi-gloss litho sheet for sheet fed commercial toner fusion digital presses with blockout barrier		
	<b>Typical Physical Properties of Face Stock without Adhesive</b>		
	Caliper, inches	0.0031 +/- 10%	TAPPI T-411
	Opacity %	99.5	TAPPI T-425
	Basis Weight, lbs. (25" x 38"/500 sheets)	60+/- 10%	TAPPI T-410
<b>Adhesive</b>	General Purpose Permanent bonds well to a wide variety of surfaces. It is especially formulated to all but eliminate sheet edge adhesive bleed.		
	<b>Typical Physical Properties of Adhesive</b>		
	Thickness, inches	0.0006 +/- 10%	
	Peel Adhesion, lbs./in.	2.0	PSTC-2 (30 min. applied)
	Temperature Ranges		
	Minimum Application	+35°F (1.6°C)	CTM #45 Curwood
	Service Ranges	-65°F to +180°F (-54°C to +82°C)	Polyester Film Dry Surface
<b>Liner</b>	A cost effective white kraft liner has outstanding lay-flat characteristics and internal strength, toughness, tear resistance for kiss cutting.		
	<b>Typical Physical Properties of Liner</b>		
	Caliper, inches	0.0042+/- 10%	TAPPI T-411
	Basis Weight, lbs. (24" x 36"/500 sheets)	72 +/- 10%	TAPPI T-410
<b>Total Caliper</b>	0.0079 ± 10% inches (7.9 mils)		
<b>GSM</b>	231 ± 10%		
<b>Printing Process</b>	Sheet fed commercial toner fusion presses.		
<b>Shelf Life</b>	Two years when stored at 72° F and 50% R.H.		

This product complies with CONEG regulations.

**IMPORTANT NOTICE:** The information given and recommendations made herein are based on our research and are believed to be accurate. In every case, user shall determine before using any product in full scale production, whether such product is suitable for their particular purpose under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability, expressed or implied. User assumes all risk and liability whatsoever in connection with their use of any product. When used as recommended in this Performance Guide, some types of graphics and end uses may be warranted by the Mactac Open Image Warranty™. Contact Mactac for specific warranty information. Ultimately, sellers and manufacturers only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

™ Trademark of Morgan Adhesives Company LLC

® Registered Trademark of Morgan Adhesives Company LLC

[www.Mactac.com](http://www.Mactac.com)

